	b					
						Cons. Division
Form 3 160-5 (June 1990)	UN DEPARTME BUREAU OF		INTERIOR		-	Budget Bureau No. 1004-0135
SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.					LC 057210 6. If Indian, Allottee or Tribe Name	
Lo not use this ic	Jse "APPLICATION F(DR PERMIT-	pen or reentry —" for such pr	oposals	erent reservoir.	
SUBMIT IN TRIPLICA TE					7. If Unit or CA, Agreement Designation	
1. Type of Well Image: Second seco					8. Well Name and No. MCA Unit #120	
Conoco Inc 3. Address and Telephone No.					9. API Well No.	
10 DESTA DR. STE. 100W, MIDLAND, TX 79705-4500 (915) 686-5580					30-025-00720 10. Field and Pool, or Exploratory Area	
 Location of Well (Footage. Sec., T. R. M. or Survey Description) 660' FNL & 1980' FWL, Sec. 27, T17S, R32E, C 					Maljamar Grayburg/SA 11. County or Parish, State Lea, NM	
In CHECK A	PPROPRIATE BOX	s) TO INDI	CATE NATUR	REOFN	OTICE, REPOR	RT, OR OTHER DATA
TYPE OF SUBMISSION TYPE OF ACTION						
3. Describe Proposed or Comp	nt Report	1 9 2001 3LM	C D D D D D D D D D D D D D D D D D D D	k ir Instal	ed Liner stimated date of starting	Change of Plans New Construction Non-Routine Fracturing Water Shut-Off Conversion to Injection Dispose Water Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) any proposed work. If well is directionally drilled
3/26/01 RIH w/4 1/2		Circulate the h	hole with 80 bb	ls of fresh	water and remove	old wellhead and put 8 5/8 well-

Pick up backer 4 1/2 single valve float collar with baffle plate w/4 1/2 aluminum nose guide with cementing ports w/4 1/2 fl4s
premium threads and 80 joints of 4 1/2, 10.5# casing with fl4s flush joint threads. Tag top of liner @ 3338'. Set slip in 8 5/8
wellhead and cut off casing and weld 4 1/2 bell nipple on casing. RU BJ Services and circ 55 bbls of fresh water; break circ.
(casing was empty). Pumped 17.9 bbls 76 sx slurry of 14.8 ppg cement. Dropped wiper plug and pumped 53 bbls; had 1.5 bbls
of cement seen at pit. Bumped plug and SD. Left 1800# on casing; max pressure was 1800#; max rate was 1.5 bpm.

3/28/01 Pick up 3 7/8 bit, 4 drill collars, tagged cement @ 3308'. Drilled out 20' cement and wiper plug and baker tool. RIH to 3500' & wash sand off RBP. POOH w/bit and stand back drill collars. SD

3/29/01 RIH w/ret. head and tag @ 3494'; could not latch onto packer. RU rev. unit. Washed over 4' & could not go any further. POOH w/retrieving head. RIH w/short head retrieving head and try to latch onto packer. Could not latch onto packer. POOH w/ret. head and RBIH w/flat shoe and RIH above fish to 3440' and SD.

3/30/01 Tagged up @ 3494', clean out to 3500'. Had aluminum sheaving in returns. POOH w/wash over tool and RIH w/short catch retrieving head. Latch onto packer and release. POOH w/H valve and top collar of packer. SD

4/2/01 RIH w/tapper swedge to 3380' and tagged RBP and RIH to PBTD 4119'; no fill. POOH w/packer. Lay down drill collars and rig down retrieving unit. RIH w/1- 2 7/8" mud joint w/2 3/8" collar, 1 jt. of IPC and 131- 2 3/8" tubing. Land SN @ 4033'. NUBOP and flange up wellhead. RIH w/2 x 1.25 x 16' RHBC pump, 1- 1.25 K-bar and 158- 3/4" c rods. Hang on and rig down.

Reesa R. Wilkes	
Title Regulatory Specialist	Date 4/10/01
Title	Date
LD, FILE ROOM	
	— Title Regulatory Specialist

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

50