

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPlicate
(Other instructions
verse side)

Budget Bureau No. 1004-1
Expires August 31, 1985
5. LEASE DESIGNATION AND SERIAL

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT-" for such proposals.)

RECEIVED
OCT 13 11 03 AM '89

LC-057210
6. IF INDIAN, ALLOTTEE OR TRIBE NAME

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Conoco Inc.

3. ADDRESS OF OPERATOR

P.O. Box 460 - Hobbs, NM 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)

At surface

Unit I

1980' FSL & 660' FEL

14. PERMIT NO.

30-025-00721

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

7. UNIT AGREEMENT NAME

MCA Unit Bly 3

8. FARM OR LEASE NAME

9. WELL NO.

#186

10. FIELD AND POOL OR WILDCAT

Maljamar G-SA

11. SEC. T., R., S., OR BLK. AND
SURVEY OR AREA

27, T1TS, R32E

12. COUNTY OR PARISH 13. STATE

Lea NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other) Puddle Pack

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

8-21-89 Jet wash OH section 3555'-3751'. Acidize w/50 Bbls
HCL-NE-FE. Pump 62 Bbl resin slurry 3555'-4195'. D.O.
resin pack 3952-4186'. Drill new hole 4195'-4250'.
Underream 3800'-4125'. Run 4 1/2" liner to 4250' and
set w/350 sx (50/50 poz). DO cmt 2820'-3326' (TOL).
DO cmt 3326'-4249'. Perf. 6th & 7th zones w/1 JS PF:
4008'-58', 4064'-92', 4102'-06', 4110'-15', 4132'-35',
4172'-76', 4186'-4206'. Acidize w/122 Bbl 15% HCL-NE-FE.
Sand frac. G1H w/prod. equip.

NOV 01 1989

Adm
CARLSBAD, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

W.W. Baker

TITLE

Administrative Supv

DATE

Oct 9, 1989

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side