

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ gas ☐ other ☐
well well well
2. NAME OF OPERATOR
Continental Oil Company
3. ADDRESS OF OPERATOR
Box 460, Hobbs, N.M. 88240
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: *660' FNL + 1980' FEL*
AT TOP PROD. INTERVAL: *Same*
AT TOTAL DEPTH: *Same*
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

☐
☐
☐
☐
☐
☐
☐
☐
☐
☐

X Inst. 4" FJ CSG

5. LEASE
LC-057210

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME
MCA

8. FARM OR LEASE NAME
MCA UNIT

9. WELL NO.
117

10. FIELD OR WILDCAT NAME
Molt, G-SA

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 28 T-17S, R-32E

12. COUNTY OR PARISH
Lea

13. STATE
N.M.

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
4000' DF

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Rigged up Work over Rig 12-12-77 and Pulled Prod. Equip + Tbg. Ran 4 3/4" Bit and Tagged Bottom AT 4100' and Circ Hole. Set a open Hole Bridge Plug AT 3680' with 2 SX Sand on top and Tested to 1000 PSI, Held OK. Ran 92 JTS of 4" FJ, K-55, 10.464 CSG Set AT 3663', CMTD w/ 200 SX Class "C" CMT. Plug Down AT 1:25 P.M. 12-14-77. Tagged CMT AT 3622' and Drilled out to the float shoe and tested CSG to 1000 PSI, Held OK. Drilled out the OHBP and Pushed TO TD AT 4100'. Ran 2 3/8" Tbg set AT 3717' with Sealing Nipple AT 3686'. Inst. Pumping Equipment and Released Rig, Completed Pumping

Subsurface Safety Valve: Manu. and Type

Set @

12-20-77

18. I hereby certify that the foregoing is true and correct

SIGNED

Wm. A. Butterfield

TITLE

Admin. Supv.

DATE

12-21-77

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

DEC 24 1977

J. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

*See Instructions on Reverse Side

USGS-5, MCA-4, File, MMS