

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPI
(Other instructions
verse side)

FE-
re

Budget Bureau No. 1004-0135
Expires August 31, 1985

5. LEASE DESIGNATION AND SERIAL NO.

LC-057210X

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1.

OIL WELL ☐ GAS WELL ☐ OTHER ☒ Injection

2. NAME OF OPERATOR

Conoco Inc.

3. ADDRESS OF OPERATOR

P.O. Box 460 - Hobbs, New Mexico 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

1980' FNL & 660' FEL - Unit Letter H

7. UNIT AGREEMENT NAME

MCA Unit

8. FARM OR LEASE NAME

MCA Unit 21y 3

9. WELL NO.

150

10. FIELD AND POOL, OR WILDCAT

Malamian G-SA

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

28-17S-32E

14. PERMIT NO.

30-025-00740

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

12. COUNTY OR PARISH

Lea

13. STATE

NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Cement to Cased Hole

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.)

MIRU. POCH w/Hog & pka. CO scale bridges in esq. DO cement &
junk to 4034'. Spot cement plug w/87 sxs cement. Tag TOC at 3524'.
DO cement & metal from 3652'-3809'. Spot 35 sxs cement. DO cement
from 3318'-3587'. G/H w/whipstock to 3588'. Set & shear. Mill from
3571'-73'. DO to 4157'. Set float shoe at 4150' & "GT" pka at 3389'.
Cement liner w/90 sxs 50/50 Pozmix class "C" cement. Set liner hanger.
G/H w/bit & scraper. CO to TOC at 3389'. Cut off 6 3/4" & 5 1/2" esq. Cmt
to surface. Run GR-CBL-CCL from 3300'-4134'. Run Newton Log.
Perf w/1 jspF at 4061'-4119', 3904'-4008' & 3822'-3849'. G/H w/
2 3/8" Hog. Test to 2000 psi. Return to injection.

18. I hereby certify that the foregoing is true and correct

SIGNED

[Signature]

TITLE Administrative Supervisor

DATE July 14, 1988

(For Bureau or Federal or State office use)

APPROVED BY

COMMENTS OF APPROVAL, IF ANY:

TITLE

DATE

[Signature]
JUL 21 11 50 AM '88
RECEIVED

*See instructions on Reverse Side

Section 106 of the National Historic Preservation Act makes it a crime for any person knowingly and willfully to make any statement or representation as to any matter within its jurisdiction.

BLM-Carlsbad (6) OXU (1) FPO (1) File