

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	State ☐ Federal ☒ Private ☐
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL ☐ GAS WELL ☐ OTHER ☒ <u>Injection</u>	7. Unit Agreement Name <u>MCA Unit</u>
2. Name of Operator <u>Conoco Inc.</u>	8. Farm or Lease Name <u>MCA Unit Bty 3</u>
3. Address of Operator <u>P.O. Box 460 - Hobbs, New Mexico 88240</u>	9. Well No. <u>150</u>
4. Location of Well UNIT LETTER <u>H</u> , <u>1980</u> FEET FROM THE <u>north</u> LINE AND <u>660</u> FEET FROM THE <u>east</u> LINE, SECTION <u>28</u> TOWNSHIP <u>17S</u> RANGE <u>32E</u> NMPM.	10. Field and Pool, or Wildcat <u>Maljamas G-5A</u>
15. Elevation (Show whether DF, RT, GR, etc.)	12. County <u>Lea</u>

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK ☐	REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐	COMMENCE DRILLING OPNS. ☐
PULL OR ALTER CASING ☐	CASING TEST AND CEMENT JOBS ☐
OTHER ☐	OTHER <u>Convert To Cased Hole</u> ☐
PLUG AND ABANDON ☐	ALTERING CASING ☐
CHANGE PLANS ☐	PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

MIRU. POOH w/ Hg & pkr. CO scale bridges in csq. DO cement & junk to 4034'. Spot cement plug w/ 87 sxs cement. Tag TOC at 3524'. DO cement & metal from 3652'-3809'. Spot 35 sxs cement. DO cement from 3318'-3587'. G/H w/ whipstock to 3588'. Set & shear. Mill from 3571'-73'. DO to 4157'. Set float shoe at 4150' & "GT" pkr at 3389'. Cement liner w/ 90 sxs 50/50 Pozmix class "C" cement. Set liner hanger. G/H w/ bit & scraper. CO to TOC at 3389'. Cut off 6 3/4" & 5 1/2" csq. Cement to surface. Run C-R-CBL-CCL from 3300'-4134'. Run Neutron log. Perf w/ 1 spf at 4061'-4119', 3904'-4008' & 3822'-3849'. G/H w/ 2 3/8" Hg. Test to 2000 psi. Return to injection.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED [Signature] TITLE Administrative Supervisor DATE July 14, 1988

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY:
MMCCO - Hobbs (3) L.L.