

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC-057210

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☐ OTHER ☒ *Water Injection*

2. NAME OF OPERATOR
Continental Oil Company

3. ADDRESS OF OPERATOR
Box 460 Hobbs, New Mexico 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

1980' FNL and 660' FEL of Sec 28

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

4003' gr

7. UNIT AGREEMENT NAME

MCA

8. FARM OR LEASE NAME

MCA Unit

9. WELL NO.

150

10. FIELD AND POOL, OR WILDCAT

Malg G-5A Reporo

11. SEC., T. R., M., OR BLK. AND SURVEY OR AREA

Sec 28, T-17S, R-32E

12. COUNTY OR PARISH

Lea

13. STATE

N. Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

PULL OR ALTER CASING ☐

FRACTURE TREAT ☐

MULTIPLE COMPLETE ☐

SHOOT OR ACIDIZE ☒

ABANDON* ☐

REPAIR WELL ☐

CHANGE PLANS ☐

(Other) *Set liner*

☒

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐

REPAIRING WELL ☐

FRACTURE TREATMENT ☐

ALTERING CASING ☐

SHOOTING OR ACIDIZING ☐

ABANDONMENT* ☐

(Other) ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Set open hole packer at $\pm 3870'$. Treat w/ 3000 gals 15% HCL-NE acid. Set $4\frac{1}{2}"$, 9.4# casing at 3793'. Cement w/ 125 sacks of Class C cement. Wait on cement 18 hours. Drill out shoe and pressure test to 750 psi.

18. I hereby certify that the foregoing is true and correct

SIGNED

Robert Gault

Administrative Supervisor

TITLE

DATE

7-24-72

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

USGS(5)

FILE

MCA(3)

*See Instructions on Reverse Side

RECEIVED

AUG 10 1972

OIL CONSERVATION COMM.
HOUSTON, N. M.