

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE
(Other instructions
reverse side of form)

Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☐ OTHER ☒ <u>Injection Well</u>	7. UNIT AGREEMENT NAME <u>MCA Unit</u>
2. NAME OF OPERATOR <u>Conoco Inc.</u>	8. FARM OR LEASE NAME <u>MCA Unit Bly 2</u>
3. ADDRESS OF OPERATOR <u>P.O. Box 460 - Hobbs, New Mexico 88240</u>	9. WELL NO. <u>175</u>
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface <u>1980' FSL & 660' FWL - Unit Letter L</u>	10. FIELD AND POOL, OR WILDCAT <u>Maljamar G-SA</u>
14. PERMIT NO. <u>30-025-00741</u>	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA <u>28-17S-32E</u>
15. ELEVATIONS (Show whether DF, RT, GR, etc.)	12. COUNTY OR PARISH <u>Lea</u>
	13. STATE <u>NM</u>

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF ☐	PULL OR ALTER CASING ☐	WATER SHUT-OFF ☐	REPAIRING WELL ☐
FRACTURE TREAT ☐	MULTIPLE COMPLETE ☐	FRACTURE TREATMENT ☐	ALTERING CASING ☐
SHOOT OR ACIDIZE ☐	ABANDON* ☐	SHOOTING OR ACIDIZING ☐	ABANDONMENT* ☒
REPAIR WELL ☐	CHANGE PLANS ☐	(Other) <u>Convert to Cased Hole</u>	
(Other) ☐			

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Work started 3/8/88. MIRR. Run CSG scraper to 3678'. Test CSG to 2000 psi. Jet wash 3816' - 3956'. Clean out to TD. Run GR-OIT caliper & inj profile. Run liner & land float shoe at 4106'. Cement w/25% 50/50 poz mix class "C" cement at 2.5 BPM w/800 psi. 1" H w/liner. 6-1/4" H w/liner to 3917'. Cld not get down. Drill out & circ clean to TD. Set liner. Ran pkr test liner to 2000 psi. Perf w/2.5 spf from 4020' - 3886'. Acidize w/15% HCL-NE-FE acid. Rig down.

18. I hereby certify that the foregoing is true and correct

SIGNED DF FINNEY

TITLE Administrative Supervisor

DATE May 18, 1988

This space for Federal or State office use

APPROVAL OF
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

*See instructions on Reverse Side

515

CALUSADO, NEW MEXICO

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

B2m-Calulad (6) OXY (1) FPCO (1) File