

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPPLICATE
(Other instructions on reverse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC-0 57210

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☐ OTHER ☒ <u>Water Injection</u>	7. UNIT AGREEMENT NAME <u>MCA</u>
2. NAME OF OPERATOR <u>Continental oil Co.</u>	8. FARM OR LEASE NAME <u>MCA Unit</u>
3. ADDRESS OF OPERATOR <u>Box 460 Hobbs, N. Mexico</u>	9. WELL NO. <u>175</u>
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface <u>1980' FSL and 660' FWL of Sec 28</u>	10. FIELD AND POOL, OR WILDCAT <u>Mel G - SA Repress</u>
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, GB, etc.) <u>3959' df</u>
	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA <u>Sec 28, T-175, R-32E</u>
	12. COUNTY OR PARISH <u>Lea</u>
	13. STATE <u>N. Mexico</u>

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETION

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Set 4 1/2" 10.23# casing at 3796'. Cemented w/ 100 socks
Class C cement. Drilled plug and cmt to 3793'.
Perf 4 1/2" casing w/ 1/2 spf from 3756'-3760'. Pumped
150 socks class C cement down casing and
displaced to 3636'. Dild cmt to 3793' and tested
squeeze w/ 1000 psi's held o.k. Perf w/ 1/2 spf from
3710'-3714'. Squeezed perfs 3710'-14' w/ 75 socks
Class C cement. Completed - 11-16-72

18. I hereby certify that the foregoing is true and correct

SIGNED

Robert Gault III

TITLE

Admin. Supervisor

DATE

12-15-72

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

ACCEPTED FOR RECORD

DEC 18 1972

U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

*See Instructions on Reverse Side

11565-5 MCA-3 File