

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIP
(Other instructions
verse side)

TE
re

Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985

RECEIVED
JUL 21 11 43 AM '88

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐	7. UNIT AGREEMENT NAME MCH Unit
2. NAME OF OPERATOR Conoco Inc.	8. FARM OR LEASE NAME MCH Unit Bly 3
3. ADDRESS OF OPERATOR P.O. Box 460 - Hobbs, New Mexico 88240	9. WELL NO. 176
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1980' FSL & 1980' FWL - Unit Letter K	10. FIELD AND POOL, OR WILDCAT Maljamar G-SA
14. PERMIT NO. 30-025-00742	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA 28-17S-32E
15. ELEVATIONS (Show whether DF, RT, GR, etc.)	12. COUNTY OR PARISH Lea
	13. STATE NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐	PULL OR ALTER CASING ☐
FRACTURE TREAT ☐	MULTIPLE COMPLETE ☐
SHOOT OR ACIDIZE ☐	ABANDON* ☐
REPAIR WELL ☐	CHANGE PLANS ☐
(Other) ☐	

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐	REPAIRING WELL ☐
FRACTURE TREATMENT ☐	ALTERING CASING ☐
SHOOTING OR ACIDIZING ☐	ABANDONMENT* ☐
(Other) ☒ Cement to Case Hole	

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Work started on 4/15/88. Cement csq leak from 887'-915'. Drill out cement. DO jet wash to 4019'. G1H w/ Hg to 4032'. Spot 60 bbls of 15% HCL-NE-FE acid from 3700'-4032'. Pump 45 bbls resin pack. Drill out resin pack from 3447'-4041'. Mill to 4061'. G1H w/ underreamer. Lean from 3950'-3642'. G1H at bit. Drill out to 4081'. Set flush, it csq at 4079' w/ 70 sxs PS light "C" cement. Drill out & G1H w/ lue back. Tie back csq & set w/ 125 sxs class "C" neat. Run GR-CBL-CCL from 3150'-4079'. Perf from 4036'-3920'. Acidize & sand frac. Circ clean. Run producing equipment & place on production. Work completed on 6/15/88.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Administrative Supervisor

DATE July 14, 1988

(This space for Federal or State office use)

APPROVED BY

TITLE

COMMENTS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

DATE JUL 27 1988
JUL 27 1988

*See instructions on Reverse Side

CARLSBAD, NEW MEXICO

Section 1001, Title 18, U.S.C., makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

BLM-Carlsbad (6) OXU (1) FPO (1) T. L.