

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPPLICATE
(Other instructions on
reverse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC 057210

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☐ OTHER ☒ Injection Well
2. NAME OF OPERATOR Continental Oil Company
3. ADDRESS OF OPERATOR Box 460 Hobbs, New Mexico
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

7. UNIT AGREEMENT NAME

MCA

8. FARM OR LEASE NAME

MCA Unit

9. WELL NO.

207

10. FIELD AND POOL, OR WILDCAT

Mali G-SA Repress

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec 28, T-17S, R-32E

12. COUNTY OR PARISH

Lea

13. STATE

N. Mexico

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3954' df

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☒

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON* ☐

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other) ☐

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

This Sundry notice replaces the one approved on 1-4-72.
It is proposed to run 4 1/2" casing (13.04# or 14.98#) from surface to 3899'. Cement w/ 80 socks class C cement and follow w/ 50 socks class C cement. Drill cement plug to 3905'. Set Squeeze packer at 3850'. Squeeze shoe w/ 50 socks class C cement. Plug back on injection.

18. I hereby certify that the foregoing is true and correct

SIGNED

[Signature]

TITLE

Admin. Supervisor

DATE

3-9-72

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

APPROVED

DATE

MAR 10 1972

ANTHONY R. BROWN
DISTRICT ENGINEER

*See Instructions on Reverse Side

USGS(5) MCA(3) File

RECEIVED

MAR 14 1972

OIL CONSERVATION COMM.
HOBBS, N. M.