

COPY TO O. C. C.

Form 9-331
Dec. 1973

Form Approved.
Budget Bureau No. 42-R1424

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☐ other P&A

2. NAME OF OPERATOR
Conoco Inc.

3. ADDRESS OF OPERATOR
P.O. Box 460, Hobbs, NM 88240

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 660' FSL @ 1980' FEL
AT TOP PROD. INTERVAL: Same
AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐

SUBSEQUENT REPORT OF:

(other) re-enter & re-plug ☒

5. LEASE

LC - 057210

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

MCA

8. FARM OR LEASE NAME

MCA Unit

9. WELL NO.

208

10. FIELD OR WILDCAT NAME

Maljano G-5A

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 28, T-17S, R-32E

12. COUNTY OR PARISH

Lea

13. STATE

N.M.

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

MIRU 4-30-80 & cut off P&A marker. Drilled out cmt. & found hole in pipe @ 27'.

Pumped 35 sx. class "C" cmt. down 7" csg. Circ'd cmt. Drilled out cmt. to

1100'. Did not tag cmt. plug @ 2080' to 2115'. Tagged cmt. retainer @ 2116'.

Ran Sonic log - water flow isolated to salt section. Spotted 30 sx. cmt. on

top of retainer. Pulled up the hole to 1250' & spotted 140 sx. plug to

surface. Squeezed an additional 30 sx. into holes @ 28'-30'. Erected

dry hole marker & cleaned location

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED W. A. Dutton TITLE Admin. Supervisor

(This space for Federal or State office use)

RECEIVED
MAY 19 1980

APPROVED BY _____ TITLE _____
CONDITIONS OF APPROVAL, IF ANY:

USGS-S
NMFL-4
FILE

U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO