

UNIT STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLIC
(Other instructions on
reverse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC 057210

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

CONTINENTAL OIL COMPANY

3. ADDRESS OF OPERATOR

Box 460, HOBBS, N.M. 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

660' FSL & 1980' FEL OF SEC. 28

7. UNIT AGREEMENT NAME

MCA

8. FARM OR LEASE NAME

MCA UNIT

9. WELL NO.

208

10. FIELD AND POOL, OR WILDCAT

MALJ. G. SA REPRESS

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 28, T. 17S, R. 32E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3943' DF

12. COUNTY OR PARISH

LEA

13. STATE

N.M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON* ☒

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other) ☐

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

It is proposed to P&A this well by the following procedure: Squeeze hole in CSG by setting cement retainer @ ± 2100' & squeeze w/ 300 sks Class "C" cmt. Pull out of retainer & spot cmt. on top of retainer. Spot 100 sks cmt. 850'-1100' & 25 sks 200'-400' & 15 sks surface plug. Erect dry hole marker.

18. I hereby certify that the foregoing is true and correct

SIGNED

Thuf D. Agre

TITLE

SR. ANALYST

DATE

10-28-75

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

APPROVED

OCT 30 1975

ARTHUR R. BROWN
DISTRICT ENGINEER

*See Instructions on Reverse Side

11565-5, MCA-d, File