

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE*
(Other instructions
reverse side)

Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐	7. UNIT AGREEMENT NAME MCA
2. NAME OF OPERATOR CONOCO INC.	8. FARM OR LEASE NAME MCA Unit Bty 2
3. ADDRESS OF OPERATOR P. O. Box 460, Hobbs, N.M. 88240	9. WELL NO. 170
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface Unit K	10. FIELD AND POOL, OR WILDCAT Mahamar 6/5A
14. PERMIT NO. 30-025-00754	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 29-17S-32E
15. ELEVATIONS (Show whether DF, RT, GR, etc.)	12. COUNTY OR PARISH Lea
	13. STATE NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other) Repair surface water flow
(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE WORK USED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

- ① MIRU on 2-28-86, POOH w/ pump. TOF @ 3853', 50' of shot hole covered.
- ② Stacked out @ 790'. CSG collapsed @ 790'. Swaged out CSG. POOH w/ swage.
- ③ WIH w/ bit & scraper to 3471'. POOH
- ④ set RBP @ 3361', found leak between 635'-793'. Dump 3sxs sand on RBP & set pkr @ 450'.
- ⑤ Pumped 250 sxs class "H" cmt, got good returns to surface, displaced cmt w/ 7 bbls TFW. Shut-in w/ 950 psi on CSG.
- ⑥ POOH w/ pkr. TOC @ 552'. Drill out to 815' & fell thru. Press. test CSG to 500 psi for 30 min. Held OK. Circ. sand off RBP & POOH. TOF @ 3853'.
- ⑦ CO from 3803'-3833', Drill out scale bridges and fell to bottom of shot hole @ 3930'. Jet wash from 3833' to 4046' (PBTD)
- ⑧ WIH w/ prod. equip. and rigged down on 3-12-86.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Administrative Supervisor

DATE 3-12-86

(This space for Federal or State office use)

APPROVED BY

TITLE ACCEPTED FOR RECORD

DATE

CONDITIONS OF APPROVAL, IF ANY:

SWD
MAR 17 1986

*See Instructions on Reverse Side

CARLSBAD, NEW MEXICO

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

BLM-Carlsbad (WALCOG) Petro-Lewis (1) Cities (1) File