

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE
(Other instructions
verse side)Form Approved
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC-029410(a)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input checked="" type="checkbox"/> <i>Water Injection</i>	7. UNIT AGREEMENT NAME <i>MCA</i>
2. NAME OF OPERATOR <i>Continental Oil Company</i>	8. FARM OR LEASE NAME <i>MCA Unit</i>
3. ADDRESS OF OPERATOR <i>Box 460 Hobbs, N. Mex.</i>	9. WELL NO. <i>169</i>
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface <i>1980' FSL and 660' FWL of Sec 29</i>	10. FIELD AND POOL, OR WILDCAT <i>Malj G-SA Repress</i>
14. PERMIT NO.	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA <i>Sec 29, T-175, R-32E</i>
15. ELEVATIONS (Show whether DF, RT, GR, etc.) <i>3912' df</i>	12. COUNTY OR PARISH <i>Lea</i>
	13. STATE <i>N. Mexico</i>

18. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☒FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

It is proposed to shut off water in this well by the following procedures: Set open hole bridge plug at 3580' - 3590' and spot sand on top of plug to 3555' - 3565'. Set cement retainer at \pm 3450' and squeeze w/ 1000 gals SAF Mark III and 75 sacks Class C Cement. Drill out retainer and plug to 3546' and pressure test to 700 psi. Drill and push OHBP to 4060' and place back on injection.

18. I hereby certify that the foregoing is true and correct

SIGNED

Robert Bault III

TITLE

Admin. Supervisor

DATE

12-22-72

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

APPROVED

DEC 23 1972
ARTHUR J. BROWN
DISTRICT ENGINEER

*See Instructions on Reverse Side

USGS-5 MCA-3 File