

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPL
(Other instructions
verse side)FE-
re-Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC 029410 A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input checked="" type="checkbox"/> Water Injection		7. UNIT AGREEMENT NAME MCA	
2. NAME OF OPERATOR Continental Oil Company		8. FARM OR LEASE NAME MCA Unit Bly 2	
3. ADDRESS OF OPERATOR P. O. Box 450, Hobbs, New Mexico		9. WELL NO. 160	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1980' FSL & 660' FWL, Sec. 29, T-17S, R-32E, Lea County, New Mexico.		10. FIELD AND POOL, OR WILDCAT Mallamar Repress. (CSA) Pool	
14. PERMIT NO.		15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3912' D.F.	
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 29, T-17, R-32	
		12. COUNTY OR PARISH Lea	
		13. STATE N.M.	

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☒ DeepenPULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐☒ X

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

On 3-14-67 this well was converted to water injection by setting a packer at 3406'. In order to open additional Grayburg San Andres pay section to injection, it is proposed to perform the following remedial work:

1. Clean out fill to TD 3935'.
2. Deepen to a TD of 4080' by drilling 145' new hole.
3. Run Gamma-Ray-Neutron log 4080-3100'.
4. Run cement lined tubing with packer set at 3440'.
Return well to injection.

18. I hereby certify that the foregoing is true and correct

SIGNED

James A. Hart

TITLE

Supervising Engineer

DATE

8-22-67

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

USGS-5

TITLE

DATE

APPROVED

AUG 25 1967

A. M. BROWN

*See Instructions on Reverse Side DISTRICT ENGINEER