

UNITED STATES DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
NEW MEXICO

Form approved
Budget Bureau No. 1004-0135
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

5. LEASE DESIGNATION AND SERIAL NO.

LC-029410A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

MCA Unit

8. FARM OR LEASE NAME

MCA Unit Bty 2

9. WELL NO.

173

10. FIELD AND POOL, OR WILDCAT

Maljamar G-5A

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

29-17S-32E

12. COUNTY OR PARISH

Lea

13. STATE

NM

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Conoco Inc.

3. ADDRESS OF OPERATOR

P.O. Box 460 - Hobbs, New Mexico 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

1980' FSL & 660' FFL - Unit Letter I

14. PERMIT NO.

30-025-00762

15. ELEVATIONS (Show whether DP, RT, GR, etc.)

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Convert To Cased Hole

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting and proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Work started 2/29/88. MIRRU. Drilled & jet wash to PBTD. Ran caliper survey. Spot 33 bbls 15% HCL-NE-FE acid from 4020'-3650'. Spot resin pack 4020'-3825'. Drill out resin pack 3830'-4020'. Drill out sand 4020'-4064'. Drill out cement 4064'-4168'. Underream 3780'-3910'. Unable to hang liner at 3212'. Set liner on bottom, float shoe 4184', landing collar 4142'. Cement liner w/175 sxs 50/50 poz mix class "C". Wash cement to top of liner. Test liner to 2500 psi. Run GR-CBL-CCL 4146' to top of liner. Perf 9th zone w/2 1/2 spf from 4099'-4142' & 7th zone from 3938'-4063' plus 3794'-3922' w/1 1/2 spf. Acidize zone. Run producing equipment & place on production.

18. I hereby certify that the foregoing is true and correct

SIGNED

D F FINNEY

TITLE Administrative Supervisor

DATE May 19, 1988

This space for Federal or State office use

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

ACCEPTED FOR RECORD

DATE

*See instructions on Reverse Side

CAILSBAD, NEW MEXICO

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

BLM-Cailsbad (6) OXY (1) FPCO (1) File