

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPlicate
(Other Instructions
Reverse Side)

Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985

5. LEASE DESIGNATION AND SERIAL NO.

LC-029410A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. ☐ OIL WELL ☐ GAS WELL ☐ OTHER <u>Injection Well</u>	7. UNIT AGREEMENT NAME <u>MCA Unit</u>
2. NAME OF OPERATOR <u>Conoco Inc.</u>	8. FARM OR LEASE NAME <u>MCA Unit Bly 2</u>
3. ADDRESS OF OPERATOR <u>P.O. Box 460 - Hobbs, New Mexico 88240</u>	9. WELL NO. <u>171</u>
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) <u>At surface</u> <u>1980' FSL & 1980' FEL - Unit Letter J</u>	10. FIELD AND POOL, OR WILDCAT <u>Majamar G-SA</u>
14. PERMIT NO. <u>30-025-00764</u>	15. ELEVATIONS (Show whether DF, RT, GR, etc.)
12. COUNTY OR PARISH <u>Lea</u>	13. STATE <u>NM</u>

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
(Other) ☐

PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
ABANDON* ☐
CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐
FRACTURE TREATMENT ☐
SHOOTING OR ACIDIZING ☐
(Other) Convert to Cased Hole

REPAIRING WELL ☐
ALTERING CASING ☐
ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Work started on 2/29/88. MURU. Test csg to 2000 psi. Clean out & pit wash to TD. Spot 30 bbls 15% HCL-NE-FE acid from 3960'-3784'. Spot resin pack from 3960'-3400'. Squeeze at 3735' w/50 sxs class "C" cement. Drill out cement retained. Drill out resin pki. from 3780'-3960' & underream to 4084'. Mill out 4" from 4084' to TD. Run fiberglass liner assy & set w/65-35 class "H" pozmix. Run GR-CBL & neutron log. Perf. 6th zone 3818'-3897' w/1 jspF; 7th zone 3912'-3945' w/1 jspF and 3982'-4030' w/2 jspF plus 9th zone 4050'-4099' w/2 jspF. Acidize and return to injection.

18. I, the undersigned, certify that the foregoing is true and correct

SIGNED Deanne D. Finney

TITLE Administrative Supervisor

DATE May 18, 1988

(Leave space for Federal or State office use)

ACCEPTED FOR RECORD

APPROVALS OF APPROVAL, IF ANY:

TITLE

DATE

*See instructions on Reverse Side

SJS
CARLSBAD, NEW MEXICO

Title 18 U.S.C. section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

BLM-Carlsbad (6) OXY(1) FPCO(1) File