

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUBMIT IN TRIPI  
(Other instructions  
verse side)

TE-  
FE-

Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

10 029410 A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen existing back to a different reservoir.  
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL ☐ GAS WELL ☐ OTHER Water Injection

2. NAME OF OPERATOR

Continental Oil Company

3. ADDRESS OF OPERATOR

P. O. Box 450, Hobbs, New Mexico

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.  
See also space 17 below.)  
At surface

1980' FSL & 1980' FEL, Section 29, T-17S, R-32E,  
Lea County, New Mexico.

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, ST, GR, etc.)

3931' DE

10. FIELD AND POOL, OR WILDCAT  
Mallamar Express.

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

Sec. 29, T-17, R-32

12. COUNTY OR PARISH 13. STATE

Lea N.M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) Deepen

PULL OR ALTER CASING ☐

MULTIPLE COMPLETES ☐

ABANDON\* ☐

CHANGE PLANS ☐

X

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other)

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT\* ☐

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any  
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-  
nent to this work.)

On 3-16-67 this well was converted to water injection by setting  
a packer at 3411'. In order to open additional Grayburg San Andres pay  
section to injection, it is proposed to perform the following remedial work:

1. Deepen from 4015' to 4090' by drilling 90' new hole.
2. Run Gamma-Ray-Neutron log 4090-3100' w/caliper over open  
hole section.
3. Run cement lined tubing with packer set at 3450'.  
Return well to injection.

18. I hereby certify that the foregoing is true and correct

SIGNED

*James A. Hart*

TITLE Supervising Engineer

DATE 8-22-67

(This space for Federal or State office use)

APPROVED BY  
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

USGS-5

\*See Instructions on Reverse Side

APPROVED  
AUG 23 1967  
A. H. BROWN  
DISTRICT ENGINEER