

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE
(Other instructions on reverse side)Form approved.
Budget Bureau No. 42-R14215. LEASE DESIGNATION AND SERIAL NO.
LC-029410(a)
6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐	7. UNIT AGREEMENT NAME <i>MCA Unit Repl.</i>
2. NAME OF OPERATOR <i>Continental Oil Company</i>	8. FARM OR LEASE NAME <i>MCA Unit</i>
3. ADDRESS OF OPERATOR <i>P.O. Box 460, Hobbs, N.M.</i>	9. WELL NO. <i>212</i>
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface <i>660 FSL + 1980' FFL of Sec 29, T-17S, R-32E, Lea Co., N.M.</i>	10. FIELD AND POOL, OR WILDCAT <i>Maj. G-SAR</i>
14. PERMIT NO.	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA <i>Sec. 29, T-17S, R-32E</i>
15. ELEVATIONS (Show whether DF, RT, CR, etc.) <i>3922 DJ</i>	12. COUNTY OR PARISH <i>Lea</i>
	13. STATE <i>N.M.</i>

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Work Done: Frased w/30,000 gal trtd gelled wtr + 45,000 # 20-40 sd. in 2 equal stages, Diverted between stages w/1000 gal trtd prod wtr. w/1000 # benzoin acid after pmgg. 200 bbls on each stage. Pump 10 bbls trtd prod. wtr. mixed w/dram United TH-763 chemical.

Drilled 6 1/8" hole to new TD of 4070'; acidized w/2500 gals 15% LSTNE acid, w/silt suspension additive.

Ran prod. equipment + placed well back on prod.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

DATE

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

4565(5) MCA(3) File

*See Instructions on Reverse Side

RECORDED

FEB 26 1971

U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO