

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE\*  
(Other instructions on reverse side)Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input checked="" type="checkbox"/>	Water Injection
2. NAME OF OPERATOR	Continental Oil Company
3. ADDRESS OF OPERATOR	Box 460 Hobbs, New Mexico 88240
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface	660' FSL and 1980' FWL of Sec 30
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3883' of

7. UNIT AGREEMENT NAME	MCA
8. FARM OR LEASE NAME	MCA Unit
9. WELL NO.	217
10. FIELD AND POOL, OR WILDCAT	Maly G-SA Repress
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA	Sec 30, T-175, R-32E
12. COUNTY OR PARISH	Lea
13. STATE	N. Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☒REPAIR WELL ☐

(Other)

PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON\* ☐CHANGE PLANS ☒

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐

(Other)

REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT\* ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Set open hole packer at 4018'-4028'. Treat w/ 2000 gals 28% HCL-NE acid. Set 4 1/2" 9.5 # casing at 3790'. Cement w/ 175 sacks of Class C cement. Wait on cement 24 hours. Drill 2-4' below shoe and pressure test to 750 psi.

18. I hereby certify that the foregoing is true and correct

SIGNED

*Robert Gault*

Administrative Supervisor

TITLE

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

USGS (5) FILE

MCA(3)

TITLE

APPROVED

JUL 26 1972

ARTHUR R. BROWN  
DISTRICT ENGINEER

\*See Instructions on Reverse Side

DATE 7-24-72