

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-71424

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT--" for such proposals.)

1. OIL WELL ☐ GAS WELL ☐ OTHER ☒ <u>Water Injection Well</u>	5. LEASE DESIGNATION AND SERIAL NO. <u>LC 029910(6)</u>
2. NAME OF OPERATOR <u>Continental Oil Company</u>	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
3. ADDRESS OF OPERATOR <u>P. O. Box 460 Hobbs, New Mexico 88240</u>	7. UNIT AGREEMENT NAME <u>MCA</u>
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface <u>1980' FSL & EL of Sec. 30, T-175, R-32E</u> <u>in Lea, County, N. Mex.</u>	8. FARM OR LEASE NAME <u>MCA Unit</u>
14. PERMIT NO.	9. WELL NO. <u>166</u>
15. ELEVATIONS (Show whether DF, RT, GN, etc.) <u>3093 DF</u>	10. FIELD AND POOL, OR WILDCAT <u>Malgam Reservoir</u> <u>G-5A Pool</u>
	11. SEC., T., R., M., OR BLE. AND SURVEY OR AREA <u>Sec. 30, T-175, R-32E</u>
	12. COUNTY OR PARISH <u>Lea</u>
	13. STATE <u>N. Mex.</u>

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETION ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

This W I W was deepened by the following procedure:

Cleaned out from 3824' to 3955'. Drilled new 6 1/4" hole from 3955' to 4066'. Ran GR/N log from TD to 3,000'. Displaced annulus with treated water and ran 2 3/8" cement lined tubing with packer. Set packer at 3314'.

Injected 850 BW in 24 hrs. with 1200# well head pressure.

V.D.S. - 5 MCA Bitumens File

18. I hereby certify that the foregoing is true and correct

SIGNED M.E. YeakleyTITLE Adm. Section ChiefDATE 2-4-69

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

APPROVED

*See Instructions on Reverse Side

FEB 6 1969

J. L. GORDON
ACTING DISTRICT ENGINEER