

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE\*  
(Other instructions on reverse side)

Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC 029410 b

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Continental Oil Company

3. ADDRESS OF OPERATOR

P. O. Box 460, Hobbs, New Mexico 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\* See also space 17 below.)

At surface

660' FNL & 660' FWL Sec. 30, T-17S, R-32E, NMPM  
Lea County, New Mexico

7. UNIT AGREEMENT NAME

MCA

8. FARM OR LEASE NAME

MCA Unit

9. WELL NO.

104

10. FIELD AND POOL, OR WILDCAT

Maljamar Repress.  
(GSA) Pool

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 30, T-17S, R-32E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3900 DF

12. COUNTY OR PARISH

Lea

13. STATE

N.M.

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Run liner & convert to inj. x

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Well was converted to inject on in the following manner:

1. Cleaned out 3718-3940' and drilled 3940-3980'.
2. Ran 645' of 4 1/2" liner casing and set at 3335-3980'.
3. Cemented with 100 sacks of class "C" cement with 1/4# flow seal a sack. Tested 750# for 30 minutes. Test OK. WOC 18 hours.
4. Cleaned out cement from 3240-3335'.
5. Ran sand jet tool and slotted liner at 3589, 3614, 3633, 3654, 3678, 3695, 3703, 3719, 3865, 3880, 3890, 3904, 3912, 3944 and 3952.
6. Cleaned out sand from 3880-3980'.
7. Treated perforations 3865-3952, 3678-3719, 3589-3654, 3589-3719', with 1000 gals. 15% LSTNE acid.
8. Set packer at 3508'.
9. November 19, 1967 injected 1250 barrels water in 24 hours..

18. I hereby certify that the foregoing is true and correct

SIGNED J. A. Gordon

TITLE District Engineer

DATE 12-4-67

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

USGS-5 PARTNERS-15 FILE

TITLE

DEC 8 1967

DATE

J L GORDON  
ACTING DISTRICT ENGINEER

\*See Instructions on Reverse Side