

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well gas ☐ well other ☐
2. NAME OF OPERATOR
Continental Oil Company
3. ADDRESS OF OPERATOR
P.O. Box 460 Hobbs, N.M.
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: *1980' FWL, 660' ENL*
AT TOP PROD. INTERVAL: *=*
AT TOTAL DEPTH: *=*

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF ☐
- FRACTURE TREAT ☐
- SHOOT OR ACIDIZE ☐
- REPAIR WELL ☐
- PULL OR ALTER CASING ☐
- MULTIPLE COMPLETE ☐
- CHANGE ZONES ☐
- ABANDON* ☐
- (other) ☐

SUBSEQUENT REPORT OF:

- ☐
- ☐
- ☐
- ☐
- ☒
- ☐
- ☐
- ☐

5. LEASE

LC 029410 B

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

mca

8. FARM OR LEASE NAME

mca Unit

9. WELL NO.

105

10. FIELD OR WILDCAT NAME

Maj. G-5a

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec 30 T-17S R-32E

12. COUNTY OR PARISH

Lea

13. STATE

N.M.

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

3912' DF

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

a liner was set in subject well as follows:

11-4-78 MIRA, inst. B.O.P.

11-5- hit tight spot in 7" csq @ 3379'

11-6- kill well, made 6" prog. w/ swedge

11-7- no prog.

11-8- mill 3377 to 3379'

11-9- mill to 3383

11-10. fallout tight spot @ 3354.
CO to 3037'

11-11 dump gravel

11-12 S.I.

11-13- dump frac sand.

11-14. with w 5", 15", 12-55 csq liner.
landed csq @ 3600' w/ top of hqr @ 3063' KB.
set w/ 75 excl. cement.

11-15 began drlg on cement.

11-19 found hole in 8 5/8" 37" csq @ 132'

11-20 sq. hole @ 132' circ to 100'

11-29. test csq to 200 psi. hold ok.

11-30 circ hole clean

12-3. pump 5000 gals 15% HCl/Na acid dispw/ 55661 TFW

12-4 log, hung well on. Rel. rig.

12-5 Begin test

Subsurface Safety Valve: Manu. and Type

Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

Wm. A. Butterfield

TITLE

Admin. Supr

DATE

12-12-78

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

UGG-5

MCA 4

FILE

ACCEPTED FOR RECORD

DEC 14 1978

U.S. GEOLOGICAL SURVEY

EDWARDS, NEW MEXICO

DEPT. OF
STATE
WASHINGTON

RECEIVED
JUL 10 1976
U.S. DEPT. OF STATE