

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE  
(Other instructions on  
reverse side)

Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.  
**LC 029410(b)**  
6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☐ OTHER ☒ **Water Injection**  
2. NAME OF OPERATOR **CONTINENTAL OIL COMPANY**  
3. ADDRESS OF OPERATOR **Box 460, Hobbs, New Mexico 88240**  
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)  
At surface **1980' FNL & 1980' FNL OF Sec. 30 1976**

7. UNIT AGREEMENT NAME **MCA**  
8. FARM OR LEASE NAME **MCA UNIT**  
9. WELL NO. **162**  
10. FIELD AND POOL, OR WILDCAT **Mali G-SA Repress**  
11. SEC., T., R., M., OR B.L.E. AND SURVEY OR AREA **Sec. 30, T. 17S, R. 32E**  
12. COUNTY OR PARISH **Lea** 13. STATE **N.M.**

14. PERMIT NO. 15. ELEVATIONS (Show whether DP, RT, GR, etc.)

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐ PULL OR ALTER CASING ☐  
FRACTURE TREAT ☐ MULTIPLE COMPLETION ☐  
SHOOT OR ACIDIZE ☐ ABANDON\* ☐  
REPAIR WELL ☐ CHANGE PLANS ☐  
(Other) **Repair Communication** ☒

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐ REPAIRING WELL ☐  
FRACTURE TREATMENT ☐ ALTERING CASING ☐  
SHOOTING OR ACIDIZING ☐ ABANDONMENT\* ☐  
(Other) ☐  
(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

**IT IS PROPOSED TO Repair Communication as follows:**

**Spot Red Gravel w/c/sol/cap in open hole to 3648'. Set cmt Retainer AT 3590' & squeezed w/100 SX class C CMT, Reverse out Excess & WOC. Drill out Retainer and cmt to 2-3' below shoe & Pressure test to 2000 PSI, clean out to 3940', Re-run cmt.-lined Inj. Tbg. & Place on Injection.**

18. I hereby certify that the foregoing is true and correct

SIGNED **Bill Penfold** TITLE **adm supervisor** DATE **9-15-76**

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

**APPROVED**  
SEP 16 1976  
**BERNARD MOROZ**  
DISTRICT ENGINEER

\*See Instructions on Reverse Side

**USGS(5), MCA(4), File**

RECEIVED

SEP 21 1976

OIL CONSERVATION COMM.  
HOBBS, N. M.