

N


1									

AREA 640 ACRES
LOCATE WELL CORRECTLY

DUPLICATE

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico



WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE.

A. H. Hoyer Et Al

Artesia, New Mexico

Company or Operator

Address

Lessee

Well No. 3-B

in NW 1/4

of Sec. 32

T. 17

R. 32

N. M. P. M.

Field, Maljamar,

Lee

County.

Well is 990 feet south of the North line and 4950 feet west of the East line of

If State land the oil and gas lease is No. B-6768 Assignment No. B-1609

If patented land the owner is Address

If Government land the permittee is Address

The Lessee is Address

Drilling commenced July 14 1941 Drilling was completed Sept. 17, 1941

Name of drilling contractor Thomas & Sons Address Artesia

Elevation above sea level at top of casing feet.

The information given is to be kept confidential until 19

OIL SANDS OR ZONES

No. 1, from 3908 to 3970 No. 4, from to

No. 2, from to No. 5, from to

No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from to feet.

No. 2, from to feet.

No. 3, from to feet.

No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED		PURPOSE
							FROM	TO	
8 1/2	32	8		1090	Texas				
5 3/16	17	10		3633	Float				

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
10	8 1/2	1090	50	Circulated		
6	5 3/16	3633	300	"		

PLUGS AND ADAPTERS

Heaving plug—Material Length Depth Set

Adapters—Material Size

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT
3 1/2		Explosive	180	9-17	3970	4000

Results of shooting or chemical treatment

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from feet to feet, and from feet to feet

Cable tools were used from 0 feet to 4005 feet, and from feet to feet

PRODUCTION

Put to producing Sept. 23 1941

The production of the first 24 hours was 175 barrels of fluid of which % was oil; %

emulsion; % water; and % sediment. Gravity, Be

If gas well, cu. ft. per 24 hours Gallons gasoline per 1,000 cu. ft. of gas

Rock pressure, lbs. per sq. in.

EMPLOYEES

A. G. Morris Driller G. C. Pratt Driller

T. O. Powell Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 24

day of September 1941

Blanche McPey

Notary Public

My Commission expires June 13-1944

Artesia N. M. 9-26 41

Place

Date

Name G. C. Pratt

Position Agent

Representing A. H. Hoyer & Etal

Company or Operator

Address Artesia N. M.

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION			
				From	To	Formation
0	10		Sand	3410	3420	Lime
10	200		Red Shale	3420	3445	Lime
200	480		Red Rock	3445	3465	Anhydrite
480	530		Red Rock Sandy	3465	3490	"
530	595		Red Rock	3490	3520	"
595	645		Red Rock	3520	3540	Lime
645	665		Red Rock	3540	3553	Anhydrite
665	680		Red Rock	3553	3560	"
680	710		Red Rock	3560	3580	Lime
710	745		Red Rock	3580	3600	Lime & Anhydrite
745	775		Red Rock	3600	3610	Anhydrite
775	800		Red Rock	3610	3625	Lime
800	820		Red Rock	3625	3633	Lime
820	835		Red Rock	3633	3635	Lime
835	850		Red Rock	3635	3645	Lime
850	865		Red Rock	3645	3655	Lime
865	875		Anhydrite	3655	3659	Lime
875	885		Anhydrite	3659	3665	Lime
885	900		"	3665	3675	Lime
900	925		"	3675	3685	Lime
925	955		"	3685	3695	Lime
955	990		"	3695	3710	Lime & Blue Shale
990	1010		"	3710	3720	Sand & Lime
1010	1065		Red Rock	3720	3730	Lime
1065	1070		Salt	3730	3740	Lime
1070	1090		"	3740	3745	Lime
1090	1105		"	3745	3755	Lime
1105	1155		"	3755	3760	Lime
1155	1170		"	3760	3765	Lime
1170	1200		Anhydrite	3765	3775	Lime
1200	1210		Salt	3775	3780	Lime
1210	1230		"	3780	3790	Lime
1230	1235		Anhydrite	3790	3800	Lime
1235	1270		Rock & Salt	3800	3815	Lime
1270	1320		Salt & Anhydrite	3815	3825	Lime
1320	1385		Salt & Anhydrite	3825	3835	Lime
1385	1395		Anhydrite	3835	3845	Lime
1395	1440		Salt	3845	3855	Lime
1440	1450		Anhydrite	3855	3865	Lime
1450	1525		Anhydrite	3865	3875	Lime
1525	1580		Salt	3875	3885	Lime
1580	1655		Salt	3885	3900	Lime
1655	1715		"	3900	3915	Lime
1715	1780		"	3915	3930	Lime
1780	1830		"	3930	3945	Lime
1830	1835		Anhydrite	3945	3955	Lime
1835	1850		Salt			
1850	1875		Salt			
1875	1890		Anhydrite & Red Rock			
1890	1910		Salt			
1910	1935		Salt, Anhydrite, Red Rock			
1935	1955		Salt	3955	3965	Lime
1955	1975		"	3965	3980	Lime, Sandy
1975	1990		"	3980	3995	Lime
1990	2045		"	3995	4003	Lime
2045	2060		Anhydrite			
2060	2070		Anhydrite			
2070	2075		"			
2075	2095		"			
2095	2125		"			
2125	2160		"			
2160	2195		"			
2195	2220		"			
2220	2255		"			
2255	2290		Anhydrite & Red Rock			
2290	2325		Anhydrite			
2325	2350		"			
2350	2385		"			
2385	2425		"			
2425	2450		"			
2450	2475		"			
2475	2505		"			
2505	2530		"			
2530	2565		"			
2565	2595		"			
2595	2615		"			
2615	2625		"			
2625	2655		"			
2655	2680		"			
2680	2705		"			
2705	2735		"			
2735	2765		"			
2765	2800		"			
2800	2815		"			
2815	2835		"			
2835	2865		"			
2865	2895		"			
2895	2915		"			
2915	2925		"			
2925	2940		"			
2940	2965		"			
2965	2990		"			
2990	3005		"			
3005	3025		"			
3025	3050		"			
3050	3075		"			
3075	3100		"			
3100	3125		"			
3125	3155		"			
3155	3170		"			
3170	3195		"			
3195	3220		"			
3220	3225		Red Sand			
3225	3230		Blue Shale			
3230	3240		Anhydrite			
3240	3260		Red Sand			
3260	3270		Red Sand			
3270	3280		Anhydrite			
3280	3300		Anhydrite			
3300	3320		"			
3320	3340		"			
3340	3355		Lime			
3355	3375		Lime			
3375	3390		Lime			
3390	3400		Lime			
3400	3410		Lime			