

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC 059001

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. ☐ OIL WELL ☒ GAS WELL ☐ OTHER

2. NAME OF OPERATOR
Continental Oil Company

3. ADDRESS OF OPERATOR
Box 460 Hobbs, New Mexico 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface FNL

660' FSE and 1980' FWL of Sec 33

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3930' gr

7. UNIT AGREEMENT NAME

MCA

8. FARM OR LEASE NAME

MCA Unit LT/3

9. WELL NO.

221

10. FIELD AND POOL, OR WILDCAT

Meli G-SA Repress

11. SEC., T./R., M., OR BLK. AND SURVEY OR AREA

Sec 33 T-175 R-32E

12. COUNTY OR PARISH

Lea

13. STATE

N. Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

Temporarily abandon X

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

It is proposed to temporarily abandon this well by the following procedures: Set cement retainer at 2710'. Pump in 300 socks lite weight cement. Set xbg at 1250' and set a 40 sock Class H Cement plug from 1250'-850'.

18. I hereby certify that the foregoing is true and correct

SIGNED

Robert Gault

Administrative Supervisor

DATE

7-3-72

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

APPROVED

JUL 6 1972

ARTHUR R. BROWN
DISTRICT ENGINEER

USGS (5) FILE

MCA(3)

*See Instructions on Reverse Side

RECEIVED

JUL 11 1962

OL CONSTITUTIONAL COMM.
HON. J. H. H.