

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well gas ☐ well other ☐
2. NAME OF OPERATOR
Continental Oil Company
3. ADDRESS OF OPERATOR
Box 460, Hobbs, N.M. 88240
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: *1345' FNL + 2615' FEL*
AT TOP PROD. INTERVAL: *Same*
AT TOTAL DEPTH: *Same*
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
~~SHOOT OR~~ ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

- ☐
☐
☒
☐
☐
☐
☐
☐
☐

5. LEASE

LC-059001

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

MCA

8. FARM OR LEASE NAME

MCA UNIT 1

9. WELL NO.

231

10. FIELD OR WILDCAT NAME

M&J, G-SA

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 33, T-17S, R-32E

12. COUNTY OR PARISH

Lea

13. STATE

N.M.

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

3929' DF

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Rigged up workover rig 9-26-77 and pulled Prod. Equip + Tbg. cleaned out to 4222' and spotted 1000 Gals of 15% Acid across the interval 4190' - 4090'. Per AT 4122', 23', 25', 27', 30', 34', 4135' w/2 JS PF. Set RBP AT 4190' and Pkr AT 4098' and pumped 1500 Gals of 15% Acid. Re-set RBP AT 4007' and Pkr AT 3797' and pumped 1500 Gals of 15% Acid. Flushed with TFW. Pulled RBP + Pkr. Ran 2 7/8" Prod. Tbg set AT 3870'; SN AT 3842'. Ran Rods + Pump. Re-l Rig 10-1-77.

Subsurface Safety Valve: Manu. and Type

Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

Wm. A. Butterfield

TITLE *ADMIN. SUPV.*

DATE

12-21-77

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

DEC 29 1977

a.g.k.

U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

*See Instructions on Reverse Side

USGS-5, MCA-4, File, MMS

RECEIVED

JUNE 1978

OIL CONSERVATION COMM.
ALBUQUERQUE, N. M.