

Form 9-331
Dec. 1973Form Approved.
Budget Bureau No. 42-R1424UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well ☐ gas ☐ well ☒ other inj.
2. NAME OF OPERATOR
CONOCO INC.
3. ADDRESS OF OPERATOR
P.O. Box 460, Hobbs, N.M. 88240
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1980' FNL & 1980' FEL
AT TOP PROD. INTERVAL: _____
AT TOTAL DEPTH: _____
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF ☐
- FRACTURE TREAT ☐
- SHOOT OR ACIDIZE ☐
- REPAIR WELL ☐
- PULL OR ALTER CASING ☐
- MULTIPLE COMPLETE ☐
- CHANGE ZONES ☐
- ABANDON* ☒
- (other) _____

SUBSEQUENT REPORT TO:

- ☐
- ☐
- ☐
- ☐
- ☐
- ☐
- ☐
- ☐

RECEIVED

1980

(NOTE: Report results of multiple completion or zone change on Form 9-330.)
U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

5. LEASE
LC-059001
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
MCA
8. FARM OR LEASE NAME
MCA Unit Bly 2
9. WELL NO.
230
10. FIELD OR WILDCAT NAME
Majmar (G-SA)
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 33, T-17S, R-32E
12. COUNTY OR PARISH LEA 13. STATE NM
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

We propose to P&A the subject well as follows:

GIH w/5 1/2" cmt. retainer set @ 3400'. Cmt. squeeze w/300sx class C. Spot 2sx on retainer. Perf @ 2150' (4TSPF). Set cmt. retainer @ 2025'. Cmt. squeeze w/125sx class C. Spot 2sx on top retainer. Run sound log to check for fluid entry. If water flow perf csg 20' above plug (4TSPF). Set retainer 75' above perfs. Squeeze w/125sx class C. Spot 2sx on top retainer. If no water perf @ 1200' and circulate class C to surface. If no circulation, perf @ 250' and circulate class C to surface. Spot 10sx class C on cmt. plug from 80' to surface. Rig down, cut off csg., erect P&A marker. Clean up location. Verbal approval received per George Stewart 9/26/80.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED [Signature] 509 Administrative Supervisor DATE 9/26/80

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:USGS 5
MCA 4
File