

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE
(Other instructions on reverse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC-02940 (a)
6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐	7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR Continental Oil Co	8. FARM OR LEASE NAME Pearcell
3. ADDRESS OF OPERATOR Box 460 Hobbs, N. Mex	9. WELL NO. 1
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 1760' FSL and 660' FUL of Sec 33	10. FIELD AND POOL, OR WILDCAT Pearcell
14. PERMIT NO.	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec 33 T-175 R-32E
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3899' df	12. COUNTY OR PARISH 13. STATE Lea N. Mex

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☒

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

This well was abandoned by the following procedure:
Set 150 sack cement plug at 2820' ^{to 3460'} Run Cement string
and set at 2116'. Cemented below retainer w/ 150 sacks
cement. Spotted 5 sacks cement on top of retainer.
Proof casing w/ 4 shots from 1124'-1125'. Pumped 80 bbl.
fresh water at 1500 psi. Did not circulate outside of
7" casing. Run 2 joints tailpipe on 2 3/8" tubing and set
at 897'. Pumped 50 sacks cement and displaced TOC to
750'. Tagged TOC at 992'. Set 10' cement plug at
surface. Installed dry hole marker and restored location.

18. I hereby certify that the foregoing is true and correct

SIGNED

Kurt Gault III

TITLE

Admin. Supervisor

DATE

10-4-72

(This space for Federal or State office use)

APPROVED

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

JAN 17 1973

*See Instructions on Reverse Side

J. I. GORDON
ATTORNEY AT LAW