

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE  
(Other instruction.  
reverse side)

Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC-029409(A)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR CONTINENTAL OIL COMPANY	8. FARM OR LEASE NAME PEARSALL AX
3. ADDRESS OF OPERATOR BOX 960 MORRIS, NEW MEXICO	9. WELL NO. 1
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1980' FSL + 650' FWL SEC 33	10. FIELD AND POOL, OR WILDCAT BAISH - MALJAMAR PEARSALL QUEN
14. PERMIT NO.	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA SEC. 33 7-175. R32E
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3899'	12. COUNTY OR PARISH LEA
	13. STATE NEW MEX

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

IT IS PROPOSED TO PLUG AND ABANDON THIS WELL DUE TO COLLAPSED CASING AT 2412'. THE FOLLOWING PROCEDURE WILL BE USED:  
RUN TBG TO 3460' AND SPOT 100 SACKS CLASS "C" CEMENT MIXED AT 14.7-14.8<sup>lb</sup>/GAL. EST. TOP OF CEMENT 2200'-2400'. CUT AND PULL 7" CSG. SPOT 100 SACKS CLASS "C" CEMENT W/8<sup>lb</sup> SALT/SACK OVER CUT-OFF CSG. SPOT 100 SACKS CLASS "C" CEMENT 900'-800' OVER BOTTOM OF SURFACE CSG. SPOT 50 SACK SURFACE PLUG 125'- TO SURFACE AND ERECT DRY HOLE MARKER. MUD BETWEEN PLUGS TO BE BRINE MIXED WITH 25 SACKS GEL PER 100 BARRELS.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE ADMIN. SUPERVISOR

DATE 7-28-72

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

APPROVED

JUL 31 1972

ARTHUR R. BROWN  
DISTRICT ENGINEER

\*See Instructions on Reverse Side

USGS(S)  
FILE