

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPPLICATE
(Other Instructions on
reverse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC-029409(a)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

CONTINENTAL OIL COMPANY

3. ADDRESS OF OPERATOR

BOX 460 HOBBS, NEW MEXICO

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

1980' FSL & 650' FWL SEC 33

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3899'

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

PEARSALL AX

9. WELL NO.

10. FIELD AND POOL, OR WILDCAT

BAISH-MALTJ.-PEARSALL
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA QUEEN

SEC 33, T-17S-R32E

12. COUNTY OR PARISH

LEA

13. STATE

NEW MEX

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☒CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

IT IS PROPOSED TO PLUG AND ABANDON THIS WELL DUE TO COLLAPSED CASING AT 2412'. THE FOLLOWING PROCEDURE WILL BE USED:

RUN TBG TO APPROX 3460' AND PUMP 75 SACKS CLASS "C" CEMENT. TAG TOP OF PLUG & IF BELOW 3390', SPOT ADDITIONAL 25 SACKS. FILL WITH MUD TO 2400'. PUMP 100 SACKS CLASS "C" CEMENT W/B #5 SALT PER SACK OVER COLLAPSED AREA. PULL TUBING AND PERFORATE W/2 HOLES AT 900'. RUN TUBING AND BRADEN HEAD SQUEEZE W/25 SACKS CLASS "C". PULL TUBING TO 150' AND SPOT 100 SACKS CLASS "C" CEMENT TO SURFACE. CAP W/ DRY HOLE MARKER AND RESTORE LOCATION.

Mud between plugs to be 9.5# (minimum) brine gel mud.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

ADMINISTRATIVE SUPERVISOR

DATE 4-20-72

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

USGS(S)

FILE

*See Instructions on Reverse Side

RECEIVED

1962

OFF. OF THE SECRETARY OF DEFENSE
WASHINGTON, D. C.