

Form 9-331a
(March 1943)

(SUBMIT IN TRIPLICATE)

Land Office Las Cruces

Lease No. 007407-4

Unit _____

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL _____	SUBSEQUENT REPORT OF WATER SHUT-OFF _____
NOTICE OF INTENTION TO CHANGE PLANS _____	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING _____
NOTICE OF INTENTION TO TEST WATER SHUT-OFF _____	SUBSEQUENT REPORT OF ALTERING CASING _____
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL _____	SUBSEQUENT REPORT OF REDRILLING OR REPAIR _____
NOTICE OF INTENTION TO SHOOT OR ACIDIZE _____	SUBSEQUENT REPORT OF ABANDONMENT _____
NOTICE OF INTENTION TO PULL OR ALTER CASING _____	SUPPLEMENTARY WELL HISTORY _____
NOTICE OF INTENTION TO ABANDON WELL _____	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Maljamar, New Mexico November 6, 1950

PEARSON "A1" LEASE

Well No. 1 is located 660 ft. from S line and 1980 ft. from W line of sec. 13

SW/4, Sec 13 17S 17E N.M.P.M.
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Pearson Lee New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 3896.5 ft.

DETAILS OF WORK

State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

This hole was dry and Application is hereby made to plug and abandon this well. We propose to fill the hole full of mud and then fill hole with cement from Total Depth of 3695' back to approximately 3575' with 24 sacks of cement. We then propose to knock off 7" casing and pull all 7" casing out of hole that is salvageable. We then propose to run tubing back in hole and spot a cement plug at the top of the remaining 7" casing with 10 sacks of cement. We then propose to spot another cement plug from the top of the Salt to approximately 1850' (which is 10' inside of 8-5/8" casing) with approximately 24 sacks of cement. We will then fill hole to the top of the 8-5/8" casing with mud. All 8-5/8" casing will be left in hole. A marker will be welded on a surge nipple which will be secured in the top of the 8-5/8" casing.

Confirming telephone conversation with Mr. Harrell of U.S.G.S., Roswell, New Mexico on 11-4-50.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Edwards Oil Company

Address P. O. Box 307

Maljamar, New Mexico

By P. A. M. Rice

Title _____

