

Form 9-331a
(March 1942)

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

RECEIVED
Land Office
Lease No. 001409-4
Nov 14 1950

OIL CONSERVATION COMMISSION
FIELD OFFICE

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF REDRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	<input checked="" type="checkbox"/>
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Maljamar, New Mexico November 14, 1950

PEABOIL "A" LEASE

Well No. 3 is located 660 ft. from [S] line and 1900 ft. from [W] line of sec. 33

SW/4, Sec 33

(1/4 Sec. and Sec. No.)

Peaboll

(Field)

17N

(Twp.)

3E

(Range)

N.M.P.M.

(Meridian)

Lee

(County or Subdivision)

New Mexico

(State or Territory)

The elevation of the derrick floor above sea level is 3094.5 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

On 11-7-50 ran tubing in hole and set 7" bit bottom and filled hole to surface with heavy mud. Then pumped in 2 1/2 sacks of cement cement from Total Depth of 3400' to 3575' and then pulled tubing back out of hole. On 11-8-50 ran McCallough Magna-Tector and found 7" casing free at 3400'. Then went in hole and cut 7" casing off at 3400' using McCallough Jet Shear and pulled 3400' of 7" OD casing out of hole. On 11-9-50 ran tubing in hole to 3430' and filled hole with mud and then spotted 10 sacks of cement cement from 3430' to 3485' and finished tubing with 10 barrels of mud. Pulled 330' of tubing out of hole, circulated with mud, and spotted 6 sacks of cement cement from 3380' to 3300' and finished tubing with 9 barrels of mud. Pulled 360' of tubing out of hole, circulated with mud, and spotted 20 sacks of cement cement from 3340' to 3290' (8-5/8" casing cut at 3290') and finished tubing with 5 barrels of mud. Removed all tubing from well and filled hole to top of 8-5/8" casing with mud. All cement was pumped in by Halliburton Oil Well Cementing Company. All 8-5/8" casing was left in hole. A piece of 6" pipe was welded on top of a surge nipple and attached in the top of the 8-5/8" casing. Well was plugged and abandoned on 11-9-50.

Company Kennecott Oil Company

Address P. O. Box 207

Maljamar, New Mexico

By R. A. McHale

Title District Superintendent

