

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
HOBBS, NEW MEXICO 88240

SUBMIT IN TRIPlicate

Budget Bureau No. 1004-0135
Expires August 31, 1985

5. LEASE DESIGNATION AND SERIAL NO.

LC-059002

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☐ OTHER ☒ <u>Injection Well</u>	7. UNIT AGREEMENT NAME <u>MCA Unit</u>
2. NAME OF OPERATOR <u>Conoco Inc.</u>	8. FARM OR LEASE NAME <u>MCA Unit Bty 3</u>
3. ADDRESS OF OPERATOR <u>P.O. Box 460 - Hobbs, New Mexico 88240</u>	9. WELL NO. <u>226</u>
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface <u>660' FNL & 660' FWH - Unit Letter D</u>	10. FIELD AND POOL, OR WILDCAT <u>Maljamar G-SA</u>
14. PERMIT NO.	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA <u>34-17S-32E</u>
15. ELEVATIONS (Show whether DF, RT, GR, etc.)	12. COUNTY OR PARISH <u>Lea</u>
	13. STATE <u>NM</u>

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐	PULL OR ALTER CASING ☐
FRACTURE TREAT ☐	MULTIPLE COMPLETION ☐
SHOOT OR ACIDIZE ☐	ABANDON* ☐
REPAIR WELL ☐	CHANGE PLANS ☐
(Other) ☐	

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐	REPAIRING WELL ☐
FRACTURE TREATMENT ☐	ALTERING CASING ☐
SHOOTING OR ACIDIZING ☐	ABANDONMENT* ☒
(Other) <u>Convert to Cased Hole</u>	

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Work started on 12/24/87. P.O.H. w/ injection equipment. Test CSG above 3709' to 2000 psi, held okay. Clean out open hole 3878'-4286'. Spot 18 bbls acid 4070'-3950'. "Puddle Pack" w/ 60 bbls. Tag resin coated sand at 3932' & spot 3 sxs sand to 3924'. Set cement retainer at 3821' & squeeze thief zone at CSG shoe w/ 5 bbls Zonelock & 75 sxs Tripropic cement. Drill out hard cement to 3919' test squeeze to 300 psi, held okay. Drill out resin coated sand to TD. Underreamed from 3925'-4294'. Jet wash from 3925'-3950'. Run 660' 2 7/8" fiberglass liner & cement w/ 130 sxs 50/50 pozmix cement w/ .75% D-60. Drill out to TD. Ran CBL & perf 2 7/8" liner from 4192'-4178' and 4152'-4020'. Run injection equipment.

18. I hereby certify that the foregoing is true and correct

SIGNED David F. Finney

TITLE Administrative Supervisor

DATE May 18, 1988

(This space for general or State office use)

APPROVAL OF
COMMISSIONS OF APPROVAL, IF ANY:

TITLE

ACCEPTED FOR RECORD
DATE

JUN 8 1988

*See instructions on Reverse Side

SJS
CARLSBAD, NEW MEXICO

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

BLM Carlsbad (6) OXY (1) FPCO (1) File