

(May 1969)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE
(Other instructions on reverse side)

Budget Form No. 42-RM-1

5. LEASE DESIGNATION AND SERIAL NO.

LC 059002

6. IF INDIAN, ACHOTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)

7. UNIT AGREEMENT NAME

MCA

8. FARM OR LEASE NAME

MCA Unit Battery

9. WELL NO.

229

10. FIELD AND POOL, OR WILDCAT

Motismen H-SAR

11. S.W., T., R., M., OR B.M. AND SURVEY OR AREA

Sec. 34, T-17, R-32E

12. COUNTY OR PARISH

Lea

13. STATE

N. Mex.

1. OIL WELL ☐ GAS WELL ☐ OTHER ☐

MAY 27 10 32 AM '69

Water Injection Well

2. NAME OF OPERATOR

Continental Oil Company

3. ADDRESS OF OPERATOR

Box 460, Hobbs, New Mexico 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.)

At surface

1980' FNL 4660 FWL of Sec 34, T-17S, R-32E,

in Lea County, N. Mex.

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, CR, etc.)

3941 DF

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Convert to water log.

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

This well was converted to water injection by the following procedures. Verbal approval to convert this well was given by Mr. Gordon on February 17, 1969.

Cleaned out well from 4234' to 4256'. Ran GR/N log with caliper log from 4256' to 3,000'. Ran 3 7/8" H-40 cement-lined tubing with packer. Displaced annulus with treated water and set packer at 3523'. Injected 500 BW in 24 hours on vacuum.

18. I hereby certify that the foregoing is true and correct

SIGNED M. E. Yeckley

TITLE Administrative Section Chief

DATE 5-16-69

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

APPROVED

MAY 20 1969

USGS-5

*See Instructions on Reverse Side

J L GORDON
ACTING DISTRICT ENGINEER