

Form 9-331a
(March 1949)

(SUBMIT IN TRIPLICATE)

Land Office Las Cruces

Lease No. 058714

Unit _____

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Pearsall "BX" # 5

34-175-32E

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	<input checked="" type="checkbox"/>
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF REDRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	<input checked="" type="checkbox"/>
NOTICE OF INTENTION TO ABANDON WELL		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Holjerman, New Mexico November 6, 1950

PEARSALL "BX" LEASE

Well No. 5 is located 660 ft. from N line and 660 ft. from E line of sec. 34

NE 1/4, NE 1/4, Sec 34
(1/4 Sec. and Sec. No.)

178
(Twp.)

377
(Range)

N. 31. 31. 4.
(Meridian)

Holjerman
(Field)

Las
(County or Subdivision)

New Mexico
(State or Territory)

The elevation of the derrick floor above sea level is 7961 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Loaded hole with water and circulated for 3 hours and on 7-20-50 ran 20 sacks of cement from Total Depth of 4316' to 4303'. On 7-21-50 ran another 20 sacks of cement from 4303' to 4319'. On 7-22-50 set Lane-Wells Type D Bridge at 3551'. Ran 3 sacks of cement on top of bridge. Top of cement 3526'. On 7-25-50 perforated casing from 3488' to 3448' with 160 - 15/32" bullets (4 per foot) using Lane-Wells Gun. On 9-2-50 perforated casing from 3470' to 3450' with 2 - 3/4" holes per foot using Lane-Wells Shotcut upon hole gun. On 9-30-50 loaded hole with oil and ran 60 quarts of liquid Nitroglycerin in 3/4" shells from 3482' to 3450.5'. Tamped shot with pea gravel and calmed. Top of Calmed 3480'. After shot cleaned well out to 3586'.

Production before Plugging back & shooting: 1 MCFD & 1 bbl of water daily.
Production after Plugging back & shooting: 6 MCFD.

Confirming telephone conversation with Mr. Pearsall, U.S.G.S., Roswell, N.M. on 9-29-50.

Company Hess Oil Company

Address P. O. Box 207

Holjerman, New Mexico

By C. P. McMill

Title District Superintendent

