

DUPLICATE

RECEIVED
NOV - 1 1951
LAND OFFICE
SERIAL NO. 111
U.S. DEPT. OF PERMIT
LAND CONSERVATION COMMISSION
OFFICE
EDGEMOORE

Las Cruces

Johns

DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

LOG OF OIL OR GAS WELL

LOCATE WELL CORRECTLY

Company Weiler Drilling Company Address P. O. Box 716, Monahans, Texas.
Lessor or Tract Johns Field Maljamar State New Mexico
Well No. 1 Sec. 32 T. 17 R. 32 Meridian _____ County Lea
Location _____ ft. {^{N.}/_{S.}} of _____ Line and _____ ft. {^{E.}/_{W.}} of _____ Line of _____ Elevation _____
(Derrick floor relative to sea level)

The information given herewith is a complete and correct record of the well and all work done thereon so far as can be determined from all available records.

Signed _____

Date _____ Title _____

The summary on this page is for the condition of the well at above date.

Commenced drilling January 27, 1941 Finished drilling July, 1941

OIL OR GAS SANDS OR ZONES
(Denote gas by G)

No. 1, from 3575 to 3587 No. 4, from _____ to _____
 No. 2, from _____ to _____ No. 5, from _____ to _____
 No. 3, from _____ to _____ No. 6, from _____ to _____

IMPORTANT WATER SANDS

No. 1, from 770 to 780 No. 3, from _____ to _____
No. 2, from _____ to _____ No. 4, from _____ to _____

CASING RECORD

[illegible]

MUDDING AND CEMENTING RECORD

[illegible]

PLUGS AND ADAPTERS

Heaving plug—Material	Length	Depth set
Adapters—Material	Size	

SHOOTING RECORD

Size	Shell used	Explosive used	Quantity	Date	Depth shot	Depth cleaned out
5 in		Oil Field explosives	150t.		3587	

TOOLS USED

Rotary tools were used from _____ feet to _____ feet, and from _____ feet to _____ feet.

Cable tools were used from _____ feet to _____ feet, and from _____ feet to _____ feet.

DATES

Put to producing July 1941

The production for the first 24 hours was 35 barrels of fluid of which % was oil, oil % emulsion, % water, and % sediment. API Gravity, °Bé. 36

If gas well, cu. ft. per 24 hours _____ Gallons gasoline per 1,000 cu. ft. of gas _____

Rock pressure, lbs. per sq. in. _____

EMPLOYEES

Edwards	1948	Driller
Sands	1948	Driller

FORMATION RECORD

FROM	TO	TOTAL FEET	FORMATION
0	55	55	Red Rock
55	115	160	Red Rock
115	300	85	Sandy Shale
300	400	100	Red Rock
400	635	235	Red Rock
635	645	10	Anhydrite
645	665	20	Red Rock
665	705	35	Red Rock
705	720	15	Water Sand
720	770	50	Sandy shale
770	780	10	Water Sand Hole full of water 770 to 780
780	850	70	Red rock & sandy shale
850	890	40	Sandy shale
890	1125	235	Red Rock
1125	1260	135	Anhydrite
1260	1266	6	Salt
1266	1275	9	Shale & anhydrite Ran 1275' of 8" casing and cemented with 50 sacks (Halliburton)
1275	1290	15	Anhydrite
1290	1295	5	Red rock
1295	1320	25	Anhydrite & salt
1320	1340	20	Red rock
1340	1365	25	Red rock & anhydrite shells
1365	1465	100	Salt & red rock
1465	1575	110	Salt

(OVER)

6745

