

OIL CONSERVATION COMMISSION

SANTA FE, NEW MEXICO

Miscellaneous Reports on Wells

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL		REPORT ON SETTING CASING	X

December 21, 1950

Monument, New Mexico

Date

Place

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO.
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the.....

Amerada Petroleum Corporation State **S "B"** Well No. **1** in the
Company or Operator Lease
C/NE/4 NE/4 of Sec. **3**, T. **15-S**, R. **33-E**, N. M. P. M.,
Saunders Field **Los** County.

The dates of this work were as follows: **December 20, 1950**

Notice of intention to do the work was ~~submitted~~ submitted on Form C-102 on **December 19,** 19 **50**
and approval of the proposed plan was (~~was~~) obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

9906' - Total Depth - Lime. Ran Schlumberger's Electrical, Gamma Ray & Microlog Surveys. Ran 244 Jts., 9889.98', 5-1/2" O.D., 17#, 8-Bd. Thd., Grade J-55 & 8640, Range 3, S.S. SH Casing - Set at 9906' & cemented with 600 sacks of Trinity Slow Set cement, mixed 3% Jell & 1/4# Flo-seal per sack. Plug to 9820' at 4:00 P.M., 12-20-50. Maximum pump pressure 2300#. Ran 6 - 5-1/2" Baker Type G Centralisers at 9890', 9860', 9830', 9800', 9790' & 9730' and 21 5-1/2" Weatherford Wall Scratchers spaced 10' apart in the above sections.

Witnessed by **C. E. Tulge** Name **Amerada Petroleum Corporation** Company **Farm Boss** Title

Subscribed and sworn before me this.....

I hereby swear or affirm that the information given above is true and correct.

21st day of **December**, 19 **50**Name **Don Tapp**Position **Assistant District Superintendent**Representing **Amerada Petroleum Corporation** Company or OperatorMy commission expires **10-11-54**Address **Drawer D, Monument, New Mexico**

Remarks:

DEC 22 1950

Ray G. Guss
Name
Title

