

OIL CONSERVATION COMMISSION

SANTA FE, NEW MEXICO

Miscellaneous Reports on Wells

OCT 27 1950

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL		REPORT ON SETTING CASING	X

October 27, 1950

Munument, New Mexico

Date

Place

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO.
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the.....

Amerada Petroleum Corporation State **S "P"** Well No. **1** in the

Company or Operator Lease
G/M/4 H/4 of Sec. **3**, T. **15-S**, R. **13-E**, N. M. P. M.,

Sanders Field **Lee** County.

The dates of this work were as follows: **October 26 & 27, 1950**

Notice of intention to do the work was (~~submitted~~) submitted on Form C-102 on **October 26,** 19**50**

and approval of the proposed plan was (~~obtained~~) obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

4247' - Total Depth - Line. Ran Schlumberger Electrical & Gamma Ray Surveys. Ran 105 Joints of 7-5/8" O.D., 26.4#, 8-Rd. Thd., Grade J-55, Range 3, S.S. casing, set at 4246' and cemented with 1000 sacks of Regular cement mixed 3% Jell, 450 sacks regular cement and 50 sacks of liner cement - total of 1500 sacks. Plug to 4169' at 4:00 A.M., 10-27-50. Maximum pump pressure 900#.

Witnessed by **D. F. Furee** **Amerada Petroleum Corporation** **Foreman**
Name Company Title

Subscribed and sworn before me this.....

27th day of **October**, 19**50**

Notary Public

I hereby swear or affirm that the information given above is true and correct.

Name **For 10/27/50**

Position **Assistant District Superintendent**

Representing **Amerada Petroleum Corporation**
Company or Operator

My commission expires **10-24-53**

Address **Drawer B, Munument, New Mexico**

Remarks:

APPROVED

OCT 27 1950

Notary Public
For 10/27/50
Name
Title