

SEP 12 1951

Date

## NEW MEXICO OIL CONSERVATION COMMISSION ECELVED

Amerada Petroleum Corporation Company or Operator

Address Drawer D, Momment, New Mexico

## MISCELLANEOUS REPORTS ON WELLS SEP

Submit this report in triplicate to the Oil Conservation Commission District Office within CH CONSERVA

	Indicate nat	ure of repor	t by checking belov	v.	
REPORT ON BEGINNI OPERATIONS		REPORT ON REPAIRING WELL			
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL			REPORT ON PULLING OR OTHERWISE ALTERING CASING		RWISE
REPORT ON RESULT ( SHUT-OFF	OF TEST OF CASING	x	REPORT ON D	EEPENING WELL	
REPORT ON RESULT (	OF PLUGGING OF WELL				
	<u> </u>	entember	10, 1951	Morrament, N	lew Mext co
		-Poemor	Date		Place
Following is a report on t	the work done and the result	s obtained u	nder the heading not	ed above at the	*******
Amerada Petroleum Corporation State			SaBa	Well No	in th
	mpany or Operatorof Sec.	1	Lease		
•					, N. M. P. M
Saunders	Pool	*********************		les	County
Notice of intention to do	the work was	mitted on F	Orm C-102 On		19
and approval of the propo	osed plan was (**********) obta DETAILED ACCOUNT OF	ined. (Cross	out incorrect words. ONE AND RESULT	S OBTAINED	
- Total Depth - 2087' - ratio bit, checked 1/2 hour befo 9827' to 9910	DETAILED ACCOUNT OF Lime. Ran Temperated actual to calcutop of cement at 98 re drilling cement and tested casing Continued with	work do ture Surlated fi 27'. To pre & connection	out incorrect words.  ONE AND RESULT  Yey - top of ( 11, 75.1%. Re  sted Gasing &  ssure drop. I  ctions for 1/2	s OBTAINED  sement bishind 5 in 2-3/8" OD Edi  connections wi  connections wi  connections with 100	gh casing at It tubing W/4, th 1000# for plug from
- Total Depth - 2087' - ratio bit, checked 1/2 hour befo 9827' to 9910 pressure drop	DETAILED ACCOUNT OF Lime. Ren Tempers of actual to calcutop of cement at 98 re drilling cement! and tested casing Continued with	work do ture Surlated fi 27'. To pre & connection	out incorrect words.  ONE AND RESULT  Vey - top of c  11, 75.1%. Re  sted Gasing & sure drop. I  ctions for 1/2  on operations	s OBTAINED  sement bishind 5 in 2-3/8" OD Edi  connections wi  connections wi  connections with 100	E casing at IR tubing W/4, th 1000# for plug from 00# - no