

DUPLICATE

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

RECEIVED

APR 11 1951

Miscellaneous Reports on Wells
OIL CONSERVATION COMMISSION
HOBBS-OFFICE

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF	X	REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL			

April 10, 1951

Monument, New Mexico

Date

Place

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO.
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the.....

Amerada Petroleum Corporation State S "C" Well No. 1 in the.....
Company or Operator Lease

C/NE/4 NE/4 of Sec. 3, T. 15-S, R. 33-E, N. M. P. M.,
Saunders Field Lea County.

The dates of this work were as follows: April 7 & 8, 1951

Notice of intention to do the work was ~~submitted~~ submitted on Form C-102 on April 5, 19 51

and approval of the proposed plan was ~~obtained~~ obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

9933' - Total Depth, 9910' Drilled Out Depth - Lime. Ram Temperature Survey - top of cement on outside of 5-1/2" casing at 6181', ratio of actual to calculated fill 87.8%. Ram 2-3/8" O.D. HUE Tubing & 4-3/4" bit & checked top of cement at 9842'. Tested casing & connections W/1200# for 1/2 hour - no pressure drop. Drilled cement plug from 9842' to 9910' & tested 5-1/2" casing & connections W/1100# for 1/2 hour - no pressure drop. Continued with completion operations.

Witnessed by G. E. Telge Amerada Petroleum Corporation Foreman
Name Company Title

Subscribed and sworn before me this.....

I hereby swear or affirm that the information given above is true and correct.

10th day of April, 19 51

Name Dr. T. T. T.

Position Assistant District Superintendent

Representing Amerada Petroleum Corporation
Company or Operator

My commission expires 10-11-54

Address Drawer D, Monument, New Mexico

Remarks:

APPROVED

Date APR 12 1951

Ray Yacharey
Name
Oil & Gas Inspector
Title

Handwritten notes in the top left corner, possibly a date or reference number.

Handwritten notes in the top right corner.

Handwritten text line in the middle of the page.

Handwritten text block in the lower middle section.

Handwritten text line in the lower middle section.

Handwritten signature or initials.

Handwritten text block below the signature.

Handwritten signature or initials.

Handwritten text line.

Handwritten text block in the bottom left corner.

Handwritten text line in the bottom left corner.

Handwritten text block in the bottom right corner.