

OIL CONSERVATION COMMISSION

SANTA FE, NEW MEXICO

JAN 15 1951

OIL CONSERVATION COMMISSION
HOBBS-OFFICE

Miscellaneous Reports on Wells

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL		REPORT ON SETTING CASING	X

January 12, 1951

Monument, New Mexico

Date

Place

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO.
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the

Amerada Petroleum Corporation State S "C" Well No. 1 in the
Company or Operator Lease

C/NE/4 NE/4 of Sec. 3, T. 15-S, R. 33-E, N. M. P. M.,
Saundera Field Lee County.

The dates of this work were as follows: January 11, 1951

Notice of intention to do the work was ~~submitted~~ submitted on Form C-102 on January 11, 1951
and approval of the proposed plan was ~~obtained~~ obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

3100' - Total Depth - Lime & Anhydrite. Ran total of 81 Joints of 8-5/8" O.D. 32# & 3 6# S.S. Casing, set at 3090' and cemented with 1000 sacks of regular cement of which 750 sacks were mixed W/3% Jell and the last 50 sacks mixed with 2 sacks of Calcium Chloride. Plug to 3024' at 6:30 P.M., 1-11-51. Maximum pump pressure 1000#. Ran 2 - 8-5/8" Baker Centralizers at 3045' & 3075' and 4 - 8-5/8" Weatherford scratchers spaced 10' apart in the above section.

Witnessed by C. E. Telge Name Amerada Petroleum Corporation Company Farm Boss Title

Subscribed and sworn before me this

13 th day of January, 1951

[Signature]

Notary Public

I hereby swear or affirm that the information given above is true and correct.

Name Don Topp

Position Assistant District Superintendent

Representing Amerada Petroleum Corporation
Company or Operator

My commission expires 10-11-54

Address Drawer D, Monument, New Mexico

Remarks:

APPROVED

JAN 15 1951

Oil & Gas Inspector

Title

1000

1000

1000

1000

1000

1000

1000

1000

1000

1000

1000