## **Energen Resources**

State "I" # 1 Lea County, New Mexico

## SUMMARY:

01/28/53 - - Spudded 13 3/8", 35.6#, J-55, @ 296' w/ 300 sks cmt, 17 1/2" hole. 02/06/53 - - Set 8 5/8", 24# & 32#, J-55, @ 4235' w/ 1500 sks cmt, 12-1/4" hole. 03/24/53 - - TD 7-7/8" hole @ 10,050' 03/25/53 - - Set 5 1/2", 15.5# & 17#, J-55 & N-80, LTC, @ 10,045' w/ 600 sks cmt, 04/01/53 - - Perforate @ 9880-9905, 9944-60', acidize w/1000 gals, IPF=175 BO x 182 BW/11 hrs 03/15/62 - - Csg leak @ 5106-37' sqz'd w/ 150 sks cmt. 03/19/62 - - Acidize w/ 4000 gals 15% LST acid + N2 + Ball Sealers. 10/03/64 - - Perforate @ 9740, 46, 69, 73, 9817, 24, 9918', 1-BSPF 10/04/64 - - Acidize w/ 2000 gals Reactol acid. 06/02/65 - - Acidize w/ 1000 gals CRA acid. 06/03/65 - - Acidize w/ 1000 gals CRA acid. 06/04/65 - - Acidize w/ 250 gals 15% NEFe acid. 08/28/80 - - CIBP @ 9600', capped with 10' sand 05/03/83 - - Ran CNL-CET-CBL 7100' to 4000' 09/02/87 - - Tagged fill or obstruction @ 4565' with tbg. Did not attempt clean out. 12/03/98 - - Fishing parted tubing--indication casing parted at 2523'-2740'. Not Repaired--FISH IN HOLE BELOW 2740' 01 -18 - 01 - - Last pull / run report: Tubing: (1/18/01)

1 - BP	0.87
1 - PS	3.00
1 - API SS-SN	0.80
83 - jts 2 7/8" J-55, 6.5# tbg	2743.30
Total	2747.90
KB Correction	10.00
EOT:	2757.97

## Rods & Pump (1/18/01)

1 - 2-1/2" X 2" X 24' RHBM w/ 6' Spray-metal plunger 68 - 7/8" Grade "K" steel rods 39 - 1" Grade "K" steel rods 1 each 1" X 4' & 6' pony rods 1 - 1-1/4" X 26' PSPR with 1-1/2" X 16' PRL

