

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE	<input checked="" type="checkbox"/>	NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)	<input checked="" type="checkbox"/>	NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

Lobbs, New Mexico
(Place)

April 16, 1963
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.....

Socony Mobil Oil Company, Inc. **New Mexico "C"** Well No. **1** in **F** (Unit)
(Company or Operator)
SE $\frac{1}{4}$ **NW** $\frac{1}{4}$ of Sec. **4**, T. **15 S**, R. **33 E**, NMPM., **Saunders Perno Penn** Pool
(40-acre Subdivision)
Las County.

FULL DETAILS OF PROPOSED PLAN OF WORK

(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

TD: 10,005'
PBD: 9940'
Csg: 10 3/4" @ 463' w/500sx; 7 5/8" @ 4950' w/2875 sx; 5 1/2" liner @ 10,005' w/1000 sx;
top of liner @ 4831'
Perfs: 9895-9903 & 9916-9926

Propose to move in & rig up pulling unit. Lower tubing below perfs. @ 9903'. Circ. hole to Brine water mixed w/2 gal. Aquaness 6786 per 1000 gals. Acidize perfs. 9895-9903 and 9916-9926 w/1000 gal. 15% NE Acid. Pull tubing and run bit. Drill out junk & bridge plug @ 9937'. Pull bit. Run 2 1/2" tbg. & pkr. Treat perfs. 9952-9968 w/3000 gal. Acid Kerosene emulsion (85% & 15%) + 32 RCN ball sealers. Pull pkr. Re-run tbg., rods & pump. Put back on production from all perfs. 9895-9903, 9916-9926 and 9952-9968.

Approved....., 19.....
Except as follows:

Approved
OIL CONSERVATION COMMISSION

By.....
Title.....

Socony Mobil Oil Company, Inc.
Company or Operator

By.....
Position.....
Send Communications regarding well to:

Socony Mobil Oil Company, Inc.
Name.....
Address.....**Box 2406, Lobbs, New Mexico**