

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

HOBBS OFFICE OCC

MISCELLANEOUS REPORTS ON WELLS

1954 MAR 29 AM 7:43

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Report by Checking Below

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF PLUGGING WELL		REPORT ON RECOMPLETION OPERATION		REPORT ON Perforate & Acidizing (Other)	X

March 26, 1954

(Date)

Lovington, New Mexico

(Place)

Following is a report on the work done and the results obtained under the heading noted above at the

Amerada Petroleum Corporation

(Company or Operator)

State S^WC^N

(Lease)

Albright Well Servicing Co.

(Contractor)

Well No. **4** in the **NW** $\frac{1}{4}$ **NE** $\frac{1}{4}$ of Sec. **9**T. **15S**, R. **33-E**, NMPM., **Saunders** Pool, **Lee** County.The Dates of this work were as follows: **March 18th - 20th, 1954**Notice of intention to do the work (was) ~~XXXX~~ submitted on Form C-102 on **March 17,** 19**54**,
(Cross out incorrect words)and approval of the proposed plan (was) ~~XXXX~~ obtained.

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

9995' DOD - Rigged up & pulled 2-3/8" OD Tubing and flow valves. Perforated 5 1/2" OD Casing from 9838' - 9848' & 9808' - 9787' w/ 1/4 bullets per foot. Re-ran 2-3/8" OD tubing with straddle packers and acidized 5 1/2" Csg. perforations from 9787' - 9808' & 9838' - 9848' w/ 1000 gals. Dowell 15% LST Acid. Re-set packers & acidized perforations 9894' - 9912' w/ 1000 gals. Dowell 15% LST Acid. Re-set packers & acidized perforations 9923' - 9928' & 9940' - 9964' w/ 1000 gals. Dowell 15% LST Acid. Pulled straddle packers & re-ran 2-3/8" OD Tubing w/ flow valves & put well on production. On Test of 3-21-54, well flowed 61 bbls oil, 210 bbls salty acid water in 24 hrs. on 1 1/4" choke w/ 600# Input gas. TP-125#.

Witnessed by **D. F. Furse**
(Name)**Amerada Petr. Corp.**
(Company)**Foreman**
(Title)Approved: **OIL CONSERVATION COMMISSION****J. G. Stanley**
(Name)

(Title)

(Date)

I hereby certify that the information given above is true and complete to the best of my knowledge.

Name **D. F. Furse**Position **Foreman**Representing **Amerada Petroleum Corporation**Address **Box 636 - Lovington, New Mexico**