

DUPLICATE

NEW MEXICO OIL CONSERVATION COMMISSION

SANTA FE, NEW MEXICO

MISCELLANEOUS NOTICES

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of notice by checking below:

NOTICE OF INTENTION TO TEST CASING SHUT-OFF	<input checked="" type="checkbox"/>	NOTICE OF INTENTION TO SHOOT OR CHEMICALLY TREAT WELL
NOTICE OF INTENTION TO CHANGE PLANS	<input type="checkbox"/>	NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING
NOTICE OF INTENTION TO REPAIR WELL	<input type="checkbox"/>	NOTICE OF INTENTION TO PLUG WELL
NOTICE OF INTENTION TO DEEPEN WELL	<input type="checkbox"/>	

Monument, New Mexico

December 29, 1951

Place

Date

OIL CONSERVATION COMMISSION,  
Santa Fe, New Mexico

Gentlemen:

Following is a notice of intention to do certain work as described below at the

**Amerada Petroleum Corporation** State **S<sup>PM</sup>** Well No. **1** in **C/NW/4, NE/4**  
Company or Operator  
of Sec. **10**, T. **15-S**, R. **33-E**, N. M. P. M. **Saunders** Field.  
**Lea** County.

FULL DETAILS OF PROPOSED PLAN OF WORK

FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS OF THE COMMISSION

10133' - Total Depth - Lime. Finished drilling 7-7/8" hole at 8:30 PM, 12/26/51.  
Ran Schlumberger's Electrical, Gamma Ray and Microlog surveys. Ran 5 1/2" Csg.  
as follows:

30 Jts 17# N-80 R-3# 8-RT SS Csg. New	1264.45'
86 Jts 17# J-55 R-2 8-RT German Csg. New	2707.28
2 Jts 17# J-55 R-2 8-RT Italian Csg. New	62.69
113 Jts 15.5# J-55 R-2 8-RT " " "	3478.68
40 Jts 17# J-55 R-2 8-RT German Csg. New	1262.24
30 Jts 17# N-80 R-3 8-RT SS Csg. New	1234.17'
<b>301</b>	<b>10009.51'</b>

Casing Set 10025' with 600 sacks Slo-Set Cement mixed 3% Jel and 1/4" Flo-Seal per sack. Plug to 9938' @ 11:50 AM, 12/28/51. Max. Pump Pressure 1250#. Ran 7 Baker Centralizers from 9856' to 10018' and 14 Weatherford Scratchers from 9865' to 10016'. Will W.O.C. for approximately 24 hours and test for casing shut-off.

Approved \_\_\_\_\_, 19\_\_\_\_  
except at follows:

**Amerada Petroleum Corporation**

Company or Operator

By *Don Tipp*  
Position **Assistant District Superintendent**  
Send communications regarding well to  
Name **Amerada Petroleum Corporation**  
Address **Drawer D, Monument, New Mexico**

OIL CONSERVATION COMMISSION,

By *Ray Younk*  
Title \_\_\_\_\_