

04-11-1952

NEW MEXICO OIL CONSERVATION COMMISSION

SANTA FE, NEW MEXICO

MISCELLANEOUS NOTICES

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of notice by checking below:

NOTICE OF INTENTION TO TEST CASING SHUT-OFF		NOTICE OF INTENTION TO SHOOT OR CHEMICALLY TREAT WELL	
NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING	
NOTICE OF INTENTION TO REPAIR WELL		NOTICE OF INTENTION TO PLUG WELL	
NOTICE OF INTENTION TO DEEPEN WELL		Plug and Abandon	XX

Hobbs, New Mexico
PlaceMarch 28, 1952
DateOIL CONSERVATION COMMISSION,
Santa Fe, New Mexico

Gentlemen:

Following is a notice of intention to do certain work as described below at the

Gulf Oil Corporation Sams State Well No. 1 in SW SE
Company or Operator Lease
of Sec. 17, T. 15S, R. 33E, N. M. P. M., Wildcat Field.
Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK

Top cement
at 1542'.

FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS OF THE COMMISSION

TD 14,126'. PBD 10,200'. 13-3/8" Casing set at 326'. 9-5/8" Casing set at 4234'.
7" Casing set at 10,625'. Top cement behind 7" casing at 9,045'. Formation Tops:
Anhydrite 1500'. Base Salt 2450'. Yates 2660'. San Andres 4185'. Glorietta 5840'.
ABO 7810'. Permo-Penn. Lime 9225'. Mississippi Lime 13282'. Woodford Shale 13925'.
Devonian 14,046'.

PROPOSED PLUGGING PROCEDURE

1. Cut off 7" casing at 9000' and pull same.
2. Cut off 9-5/8" casing at 1525' and pull same.
3. Heavy mud from 10,200' to 9,020'.
4. Cement plug from 9020' to 8940'. 26 sax cement.
5. Heavy mud from 8940' to 1545'.
6. Cement plug from 1545' to 1465'. 51 sax cement.
7. Heavy mud from 1465' to 341'.
8. Cement plug from 341' to 316'. 30 sax cement.
9. Heavy mud from 316' to 25'.
10. Cement plug from 25' to 0' and set 4" marker extending 4' above ground level. 20 sax.

Approved _____ 19_____
except at follows:

Gulf Oil Corporation
Company or Operator

By

Position

Asst. Area Prod. Supt.
Send communications regarding well to

OIL CONSERVATION COMMISSION

By

Title

Name

Address

Gulf Oil Corporation

Box 2167, Hobbs, New Mexico

Oil & Gas Inspector