

DUPLICATE

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

MISCELLANEOUS NOTICES

RECEIVED

NOV 5 1952

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL	XX	NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

Hobbs, New Mexico
(Place)

November 5, 1952
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the Lea State "H"

Gulf Oil Corporation
(Company or Operator)

Well No. 1 in P
(Unit)

SE $\frac{1}{4}$ SE $\frac{1}{4}$ of Sec. 19, T. 15-S, R. 33-E, NMPM., South Saunders Pool
(40-acre Subdivision)

Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

TD 10,904' - PBTD 10,750' - Top Salt 1650' - Base Salt 2475'
9-5/8" casing set at 4280' cemented with 1800 sacks
7" casing set at 10,560' cemented with 310 sacks

Proposed plugging procedure: 1. Set cement retainer in 7" casing at 10,520' and squeeze formation below casing shoe with 100 sacks. 2. Cut off 7" casing at approximately 8400'. 3. Spot cement plug in top of 7" casing at 8450' to 8350' with 30 sacks. 4. Cut off 9-5/8" casing at approximately 1900'. Spot cement plug in top of 9-5/8" casing at 1950' to 1850' with 60 sacks. 5. Spot cement plug from top of salt at 1650' to 1550' with 75 sacks. 6. Spot cement plug from 50' to surface and set 4" marker to extend 4' above surface. All intervals between cement plugs will be filled with heavy mud.

Approved NOV 5 1952, 19____
Except as follows:

Approved
OIL CONSERVATION COMMISSION

By Ray Yarbrough
& Gas Inspector
Title _____

Gulf Oil Corporation
Company or Operator

By R. M. Shuman

Position Asst. Area Prod. Supt.
Send Communications regarding well to:

Name Gulf Oil Corporation

Address Box 2167, Hobbs, New Mexico