(FORM C-102)
(REVISED 6-56)

NEW MEXICO OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

MISCELLANEOUS NOTICES

SUBMIT THIS NOTICE IN TRIPLICATE TO THE DISTRICT OFFICE, OIL CONSERVATION COMMISSION, BEFORE THE WORK SPECIFIED IS TO BEGIN. A COPY WILL BE RETURNED TO THE SENDER ON WHICH WILL BE GIVEN THE APPROVAL, WITH ANY MODIFICATIONS CONSIDERED ADVISABLE, OR THE REJECTION BY THE COMMISSION OR AGENT, OF THE PLAN SUBMITTED. THE PLAN AS APPROVED SHOULD BE FOLLOWED, AND WORK SHOULD NOT BEGIN UNTIL APPROVAL IS OBTAINED. SEE ADDITIONAL INSTRUCTIONS IN THE RULES AND REGULATIONS OF THE COMMISSION.

INDICATE NATURE OF NOTICE BY CHECKING BELOW

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL	X	NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (NITRO)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

Hobbs, New Mexico (PLACE) August 7, 1957 (DATE)

GENTLEMEN:

FOLLOWING IS A NOTICE OF INTENTION TO DO CERTAIN WORK AS DESCRIBED BELOW AT THE

Humble Oil & Refining Company (COMPANY OR OPERATOR) New Mexico State AQ WELL NO. 1 IN I

NE ¼ SE ¼ (40-ACRE SUBDIVISION) OF SEC. 3, T. 16S, R. 33E, NMPM., East Anderson Ranch Penn. (UNIT) POOL

Lea COUNTY.

FULL DETAILS OF PROPOSED PLAN OF WORK
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

To plug and abandon as follows:

1. Squeeze perforations from 10,860 to 10,875 feet (Below Baker packer at 10,833).
2. Cut and pull 5½-inch casing as approximately 8500 feet.
3. Place 200-foot cement plug from approximately 4350 to 4550 feet.
4. Place swage and valve in top of 13-3/8-inch casing.
5. Place marker by well as required by NMOCC.
   (Hole will be filled with a mud laden fluid).

Current Producing Interval: Perforated casing from 10,860 to 10,875.
Casing Program: 13-3/8-inch set @ 385 and cemented to surface.
9-5/8-inch set @ 4450 and cemented to surface.
5½-inch set @ 12,625 and cemented to 8555.

APPROVED _____, 19____
EXCEPT AS FOLLOWS:

Humble Oil & Refining Company
COMPANY OR OPERATOR
BY H. M'Carty
POSITION Agent
SEND COMMUNICATIONS REGARDING WELL TO:
NAME Humble Oil & Refining Company
ADDRESS Box 2347, Hobbs, N.M.

APPROVED
OIL CONSERVATION COMMISSION
BY _____
TITLE _____

dfl