

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

<p align="center">SUNDRY NOTICES AND REPORTS ON WELLS</p> <p align="center"><small>(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE APPLICATION FOR PERMIT - FORM C-101, FOR SUCH PROPOSALS.)</small></p>		<p>5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/></p> <p>5. State Oil & Gas Lease No. E-912-2</p>
<p>1. <input type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER P & A</p> <p>2. Name of Operator Atlantic Richfield Company</p> <p>3. Address of Operator P.O. Box 1978, Roswell, New Mexico 88201</p> <p>4. Location of Well UNIT LETTER P 510 FEET FROM THE South LINE AND 660 FEET FROM THE East LINE, SECTION 13 TOWNSHIP 16-S RANGE 33-E NMPM.</p>	<p>7. Unit Agreement Name Seaman Unit</p> <p>8. Farm or Lease Name Seaman Unit</p> <p>9. Well No. 1</p> <p>10. Field and Pool, or Wildcat Kennitz-Penn</p>	
<p>15. Elevation (Show whether DF, RT, GR, etc.) 4159' GR</p>		<p>12. County Lea</p>

16.

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐
OTHER ☐

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOB ☐
OTHER ☐

ALTERING CASING ☐
PLUG AND ABANDONMENT ☒

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

This well has been plugged and abandoned in the following manner:

Set 7" 24# Titan CIBP @ 11140' WLM, capped w/2 sx cement. Shot off 7" casing @ 4567' WLM, unable to pull. Shot off 7" casing @ 4442' WLM. Pulled 142 jts of 7" casing. Spotted 40 sk cement plug 4420-4590', spotted 20 sk cement plug in top of 9-5/8' casing. Installed dry hole marker. Well plugged & abandoned 3/22/71. 9# gel mud was used to spot all plugs. 9-5/8" & 13-3/8" casing strings remain intact.

Your office will be notified when location is ready for inspection.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED *W.D. Litcher* TITLE Dist. Drlg. Supervisor DATE 4-8-71

APPROVED BY *John W. Runyan* TITLE Geologist DATE MAY 5 1971

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

APR 1 1971

OIL CONSERVATION CO. INC.
HOLDS 100%